
TOLERANCE
 THIS IS A C.A.D. GENERATED DRAWING


 UNLESS OTHERWISE
 DO NOT MAKE MANUAL REVISIONS TO MASTER.

 .X
 ±0.25









.XX ±0.13 .XXX ±0.05

NOTES:


MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, 30µ" GOLD PLATED


| OPERATING TEMPERATURE: | -55°C ~ 125°C | |
|--|-----------------------------|--|
| POWER/CO-AX CONTACT RATING: (IF PRESENT) | 75Ω (IMPEDANCE) | |
| SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE: | 5A PER CONTACT 10mΩ MAX. | |
| | | |

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 5000MΩ min.

1000V AC rms



| | COMBINATION D-SUB | | SW REFERENCE NO.: 629 COMBO ASSEMBLY | | | | |
|--------------------|--|--|--------------------------------------|---------------|---------|------------|-------|
| | | | DRAWN: C | С.В | DATE: J | IAN. 01/20 | 19 |
| | | | CHECKED: | | DATE: | | |
| | EDAG INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | SCALE: (IN | N C.A.D. 1:1) | SHEET | 1 OF | 2 |
| | | | DRAWING NUMBER: 629-9W4-640-7T5 | | | | ISSUE |
| YOUR CONNECTION TO | | | PART NUMBE | ER: 629-9W4- | 640-7T5 | | 1 |





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

