



(1)





NOTES:

MATERIAL: HOUSING: SHELL: CONTACT: **OPERATING TEMPERATURE:**


.XX ±0.13

.XXX ±0.05

POWER/CO-AX CONTACT RATING: 75Ω (IMPEDANCE) (IF PRESENT)

SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.


INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:



COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY		
		DRAWN: C.B	DATE: JAN. 01/20	19
		CHECKED:	DATE:	
EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
		DRAWING NUMBER: 630-13W3640-7T3		ISSUE
		PART NUMBER: 630-13W3	3640-7T3	1

5000MΩ min.

1000V AC rms



COMPLIANT

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

STEEL, TIN PLATED COPPER ALLOY, 30µ GOLD PLATED -55°C ~ 125°C

THERMOPLASTIC POLYESTER, UL94V-0

