


Important Notice : This data sheet and its contents (the "Information") belong to the members of the EASE group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. EASE is the registered trademark of Ease Electronics Co., Limited 2019.


| PART | MOLD NO | REV NO | DATE | REVISION NOTE |
|----------|-----------------|--------|------|---------------|
| BNC PLUG | CTB001 | 1 | | |
| 5.5 PLUG | CTD004 | 2 | | |
| 5.5 JACK | CTD009 / CTD003 | 3 | | |



CABLE CONSTRUCTION


| ITEM | SPEC | |
|------------------|------------------|--------------------------------|
| CENTER CONDUCTOR | MATERIAL | BC CCA |
| | CONSTRUCT mm/No. | 0.643 (22AWG) 0.20/16 |
| INSULATION | MATERIAL | PE FOAM PE |
| | O.D. mm | 3.80±0.05 1.8± 0.05 *2C(REDBK) |
| AL/MYLAR | MATERIAL | AL/MY / |
| | MATERIAL | CCA / |
| BRAID SHIELD | CONSTRUCT mm/No. | 0.12 x 8/16 / |
| | TYPE | BRAID / |
| PVC JACKET | MATERIAL | PVC PVC |
| | O.D. mm | 6.0±0.20 4.5±0.15 |
| | COLOR | WHITE WHITE |

WIRE ADDRESS



ELECTRICAL TEST

- 1)100% OPEN SHORT&MISS WIRE TEST
- 2)INSULATION RESISTANCE:DC300V 10M OHM
- 3)CONDUCTOR RESISTANCE:3 OHM



Part Number Table

| | | | |
|-------------|-----------|--------|------------|
| Part Number | R1502BD-F | L±L1mm | 15240±60mm |
|-------------|-----------|--------|------------|

| 6 | XXXXXXXXXXXXXXXX | INNER MOLD | PE, COLOR:CLEAR | 0.015 | KG |
|-----|------------------|------------|---------------------------------|-------|------|
| 5 | XXXXXXXXXXXXXXXX | OUTER MOLD | 45P PVC, COLOR:WHITE | 0.045 | KG |
| 4 | XXXXXXXXXXXXXXXX | DC JACK | DC 5.5*2.1MM JACK/NICKEL PLATED | 1 | PCS |
| 3 | XXXXXXXXXXXXXXXX | DC PLUG | DC5.5*2.1MM PLUG/NICKEL PLATED | 1 | PCS |
| 2 | XXXXXXXXXXXXXXXX | BNC PLUG | NICKEL PLATED | 2 | SET |
| 1 | XXXXXXXXXXXXXXXX | CABLE | SEE " CABLE CONSTRUCTION " | | |
| NO. | MATERIAL NO | PART NAME | MATERIAL/FINISH | QTY | UNIT |

| STANDARD TOLERANCE LIMITS UNLESS OTHER SPECIFIED | | 單位 | MM | 比例 | 1:1 | Ease Electronics Co., Limited | | | |
|--|-------------|------------|------------|----|-----|-------------------------------|----|----|------|
| PANGE | TOLERANCE | 圖法 | Φ | 頁數 | 1/1 | 文件編號 | 客戶 | 制圖 | XIAO |
| >0-6 | ±0.08 ±0.14 | EASE料號發行日期 | 2022.08.01 | 版次 | 1.0 | R1502BD-F | 審核 | 核准 | |
| >6-30 | ±0.10 ±0.20 | | | | | | | | |
| >30-120 | ±0.20 ±0.30 | | | | | | | | |
| >120-300 | ±0.30 ±0.40 | | | | | | | | |
| >300-600 | ±0.40 ±0.50 | | | | | | | | |