

Specification Sheet

Part Number: 151-01565

Two-piece ratcheting wedge design allows for easy, positive-locking size adjustment.

Peel and stick 3M[™] VHB[™] adhesive inside clip increases grip and enables one-hand installation.

Heat-stabilized, glass-filled PA66 assembly delivers remarkable extraction force without drilling.

Three sizes cover a wide range of mounting thicknesses, reducing part inventory.

4-way, wide slot accommodates our heavy-duty and Wide-Strap Series Cable Ties.

Wedge Clip, 0.0"-0.20" Panel Thickness, PA66HSGF, Black/Green, 200/bag

Article Number 151-01565

Type BCAA

Color Black (BK) Green (GN)

Quantity Per bag

Product Description	The Wedge Clip, paired with any HellermannTyton heavy duty Cable Tie, routes cables along a frame or rail in vertical or horizontal applications. A robust design and durable materials make it ideal for extreme-duty applications. The integrated wedge mechanism slides along a stepped grade until snug against the mounting surface. Inside the clip is a 3M [™] VHB [™] (Very High Bond) adhesive pad, which actually builds strength over time. This holds the clip to the work surface instantly, enabling installers to place it into position without worrying about it falling off prior to fastening. The combination of adhesive and the clip's vice-like compression result in incredible extraction force without the need to drill holes. The Wedge Clip is offered in three sizes.
Short Description	Wedge Clip, 0.0"-0.20" Panel Thickness, PA66HSGF, Black/Green, 200/bag
Global Part Name	BCAA-PA66HSGF30-BK/GN
Length L (Imperial)	1.21
Length L (Metric)	30.8
Width W (Imperial)	1.13
Width W (Metric)	28.6
Height H (Imperial)	1.70
Height H (Metric)	43.10
Cable Tie Width Max (Imperial)	0.59
Cable Tie Width Max (Metric)	15.0

Panel Thickness Max (Imperial)

0.197

Panel Thickness	Max	(Metric)
-----------------	-----	----------

5.0

Material Polyamide 6.6, heat stabilized, glass fiber reinforced (PA66HSGF30%)

Material Shortcut PA66HSGF30

Adhesive Acrylic foam

Flammability UL 94 HB

UV Resistant (Yes/No) No

Operating Temperature -40°F to +284°F (-40°C to +140°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant Yes

Package Quantity (Imperial) 200

Package Quantity (Metric) 200

Customs Number 3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach

to product design, sustainability, producustomers. HellermannTyton operates (www.hellermann.tyton.com).				
© 2023 HellermannTyton. All Rights	Reserved. Contact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions
		·		