



1. Wiring Diagram.

P1 DVI24+5/M	P2 HD15M
15	5.10
14.16	9
8	14
7	12
6	15
C1	RED COAX 1
C2	GRAY COAX 2
C3	BULE COAX 3
C4	GREEN 13
C5	3COAX GND 6.7.8
SHELL	GND SHELL

2. Cable test condition :
 Open / Short : 100%
 Insulation resistance : 5M ohms
 Contact resistance : 2 ohm
 Hipot : DC 300V / 1 sec

3. Each pcs with PE polybag.

NO.	PART NO.	DESCRIPTION	QTY	UNIT/REF
9	PVC	45P PVC BLUE OVERMOLD	18g	P2
8	SCREW	#4-40UNC T41.2 BLUE	2	
7	CONN	HD15 BLU MALE G/F	1	P2
6	SCREW	#4-40UNC RE34 WHITE	2	
5	PE	LLDPE 500026 6201	16g	
4	PVC	45P PVC WHITE OVERMOLD	22g	
3	CORE	OD17.5*L28.5*ID9.5	2	
2	CONN	DVI24+5 MALE G/F BLK	1	P1
1	CABLE	UL2919 «1C*28AWG (7/0. 12TC) +AL+S24/0. 12TCCA» *3C+6C*28AWG (7/0. 12TC) +A+B (96/0. 12AM) +D OD8. 0 BLACK	1	3000mm

BILL OF MATERIAL

B	ADD COPPER	2021/8/24
A	INITIAL RELEASE	2014/11/12
REV/ECN	DESCRIPTION	DATE
CnC Tech,LLC		P/N: 751-20010-00300 REV B
TITLE		CBL DVI-I TO VGA 24+5-15PIN
DRAWN	WENC	DATE 08/24/21
CHECKED	EDWIN	DATE 08/24/21
APPROVAL		CUSTOMER P/N:
SHEET 1 OF 1		CUSTOMER: