## ATGBICS AT-SPLX40/1550 Allied Telesis Compatible Transceiver SFP 100Base-EX (1550nm, SMF, 40km, DOM)

Brand : ATGBICS

Product code: AT-SPLX40/1550-C

Product name : AT-SPLX40/1550 Allied Telesis Compatible Transceiver SFP 100Base-EX (1550nm, SMF, 40km, DOM)

AT-SPLX40/1550 Allied Telesis Compatible Transceiver SFP 100Base-EX (1550nm, SMF, 40km, DOM)


ATGBICS AT-SPLX40/1550 Allied Telesis Compatible Transceiver SFP 100Base-EX (1550nm, SMF, 40km, DOM):

ATGBICS AT-SPLX40/1550 100Base-EX supports a distance of up to 40km over single-mode fibre (SMF) using a wavelength of 1550nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Allied Telesis AT-SPLX40/1550= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Features	
Maximum data transfer rate *10Interface type *SFSingle-mode fiber (SMF) supported✓Multi-mode fiber (MMF) supported✓Fiber optic connectorLC	num data transfer rate * 100 Mbit/s   ace type * SFP   e-mode fiber (SMF) supported ✓   mode fiber (MMF) supported ×   optic connector LC   ransceiver standard EX   num transfer distance 40000 m   length 1550 nm   net LAN ✓   net interface type Fast Ethernet   I Diagnostics Monitoring ✓   ) ×	Certification	CE, FCC, RoHS
		Power	
		Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1.3 W
		Operational conditions	
Maximum transfer distance Wavelength Ethernet LAN Ethernet interface type Digital Diagnostics Monitoring (DDM) Wavelength-division multiplexing (WDM) Features		Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) <b>Weight &amp; dimensions</b> Width Depth Height	70 °C 0 - 70 °C -40 - 85 °C 5 - 85% 5 - 85% 13.4 mm 56.5 mm 8.5 mm
Product colour	Silver	Weight	25 g
Housing material Plug and Play	Metal ✓	Packaging data	5
Hot-Plug support Hot-swap	↓ ↓ ↓	Number of products included Package type	1 pc(s) Box
Easy to install Country of origin		Technical details	-
, ,	United Kingdom Allied Telesis	Sustainability compliance Sustainability certificates Doesn't contain	✓ RoHS Lead



5056468702005

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.