



**F1-RMS01RU2X**

## FEATURES

- Swing Out Shelf
- Holds (2) LGX Adapter Plates, Cassettes, or Modules
- Multiple Tie Downs and Cable Retention Brackets
- Flush Mount or 3.5" Protrusion; No Accessories Required
- Order Preloaded with Terminated Cables, Adapters, Pigtails or Cassettes
- Rugged 14 Gauge Aluminum, Available in Black or Off-White (BW)

The 1RU FIS Swing Out Patch Panel accommodates (2) LGX adapter plates, modules or cassettes. It is designed to house fiber terminations and accommodate patching of fiber links. The swing-out design offers easy access to cable and splices located in the patch and splice bay. Multiple cable retention brackets and tie down spots allow for convenient cable management. These units can be flush mounted or mounted with 3.5" protrusion from the rack with no additional accessories. Rack mount installs into a standard 19" rack with included mounting hardware. Adapter panels and 23" mounting brackets are sold separately.

## SPECIFICATIONS

<b>Dimensions</b>	17"W x 11.5" D x 1.75"H
<b>Capacity</b>	Up to 12 (6 Pack) or 16 (8 Pack) Simplex Connections Up to 24 (6 Pack) Duplex Connections (LC or SC)
<b>Material</b>	.060" Aluminum
<b>Coatings</b>	Electro-statically Applied Powder Coat, Available in Black or Off White

## ORDERING INFORMATION

<b>F1-RMS01RU2X</b>	1RU Swing Out Enclosure, 2 Plates, Black
<b>F1-RMS01RU2X-BW</b>	1RU Swing Out Enclosure, 2 Plates, Off White

## ACCESSORIES (PURCHASED SEPARATELY)

<b>RACK-ADP23</b>	1RU and 2RU 23" Rack Mounting Brackets, Pair, Black
<b>RACK-ADP23BW</b>	1RU and 2RU 23" Rack Mounting Brackets, Pair, Off White
<b>F1-SPL12</b>	Metal Splice Tray, 12 Position Fusion Splice Chip, 6.5"L x 4.7"W x .42"H
<b>F1-SPL24</b>	Metal Splice Tray, 24 Position Fusion Splice Chip, 11.72"L x 3.99"W x .42"H
<b>F1-6808</b>	Plastic Splice Tray, 12 Position Fusion Splice Chip, 7.1"L x 4.25"W x .48"H
<b>F1-6707BLKF</b>	Metal Splice Tray, 12 Position Fusion Splice Chip, 7.5"L x 4"W x .63"H