

**LINEAR TECHNOLOGY MATERIALS DECLARATION**

1t3483es6#trpbf

(Engineering Calculation)

TSOT-23

(printed on: 2020-07-11 17:34:27)

**TOTAL MASS (g) : 0.012595**

COMPONENT MATERIAL	VENDOR/ INDUSTRY NAMES	CONSTITUENT NAME	CAS NUMBER	CONSTITUENT MASS (g)	CONSTITUENT (PPM) OF MATERIAL	CONSTITUENT (PPM) OF TOTAL PKG.		
Active Device	Linear Technology	Silicon (Si)	7440-21-3	0.000602	1000000	47797.6679688		
Die Coat	Dow Corning	Silicone	69430-27-9	0.000000	0	0		
Lead Frame	Cu	Copper (Cu)	7440-50-8	0.004582	975000	363802.1875		
		Iron (Fe)	7439-89-6	0.000113	24000	8971.98730469		
		Phosphorus (P)	7723-14-0	0.000001	300	79.3981170654		
		Zinc (Zn)	7440-66-6	0.000003	700	238.194366455		
		Nickel (Ni)	7440-02-0	0.000000	0	0		
		Silicon (Si)	7440-21-3	0.000000	0	0		
		Magnesium (Mg)	7439-95-4	0.000000	0	0		
		Tin (Sn)	7440-31-5	0.000000	0	0		
<b>Lead Frame Total:</b>				<b>0.004699</b>	<b>1000000</b>	<b>373091.78125</b>		
Plating	PMI	Exter. Plating Pb	7439-92-1	0.000000	0	0		
		Exter. Plating Sn	7440-31-5	0.000644	1000000	51113.015625		
		<b>External Plating Total:</b>				<b>0.000644</b>	<b>1000000</b>	<b>51113.015625</b>
		Inter. Plating Ni	7440-02-0	0.000000	0	0		
		Inter. Plating Ag	7440-22-4	0.000080	1000000	6351.84960938		
		<b>Internal Plating Total:</b>				<b>0.000080</b>	<b>1000000</b>	<b>6351.84960938</b>
Die Attach	ELECTRICALLY CONDUCTIVE ADHESIVE	Silver (Ag)	7440-22-4	0.000422	750000	33506.0078125		
		Tin (Sn)	7440-31-5	0.000000	0	0		
		Lead (Pb)	7439-92-1	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.000000	0	0		
		Indium (In)	7440-74-6	0.000000	0	0		
		Metal Oxide		0.000000	0	0		
		Antimony (Sb)	7440-36-0	0.000000	0	0		
		Resin (EP)		0.000141	250000	11195.1347656		
<b>Die Attach Total:</b>				<b>0.000563</b>	<b>1000000</b>	<b>44701.140625</b>		
Encapsulation	MULTI-AROMATIC RESIN Br/Sb FREE	Resin (EP)		0.000772	130000	61295.3476562		
		Bromine (Br)	40039-93-8	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.004930	830000	391432.6875		
		Antimony Trioxide (Sb2O3)	1309-64-4	0.000000	0	0		
		Metal Hydroxide		0.000208	35000	16514.8085938		
		Carbon Black (C)	1333-86-4	0.000030	5000	2381.94360352		
		<b>Encapsulation Total:</b>				<b>0.005940</b>	<b>1000000</b>	<b>471624.84375</b>
Bond Wire Estimated	AFW/TANAKA/ Kn	Gold (Au)	7440-57-5	0.000067	1000000	5319.67382812		
					<b>TOTAL MASS (g) :</b>	<b>0.012595</b>		