

R71QR3680GY10K

Aliases (71QR3680GY10K)

R71, Film, Metallized Polypropylene, General Purpose, 0.68 uF, 10%, 1000 VDC, 105°C, Lead Spacing = 27.5mm



Click [here](#) for the 3D model.

Dimensions

L	32mm +0.3/-0.7mm
H	20mm +0.1/-0.7mm
T	11mm +0.2/-0.7mm
S	27.5mm +/-0.4mm
H ₀	18.5mm +/-0.5mm
F	0.8mm +/-0.05mm

Packaging Specifications

Packaging	T&R
Packaging Quantity	190

General Information

Series	R71
Dielectric	Metallized Polypropylene
Style	Radial
Features	PFC and Pulse
RoHS	Yes
Lead	Wire Leads
AEC-Q200	No
Component Weight	13.15 g
Miscellaneous	Above 105C DC And AC Voltage Derating Is 4%/C.

Specifications

Capacitance	0.68 uF
Capacitance Tolerance	10%
Voltage AC	275 VAC
Voltage DC	1000 VDC
Temperature Range	-40/+110°C
Rated Temperature	105°C
Dissipation Factor	0.1% 25C
Insulation Resistance	44.1176 GOhms
Max dV/dt	180 V/us
Resistance	175.5 mOhms (100kHz)
Ripple Current	1.31 Amps (100kHz 85C), 122.4 Amps (Peak)
Inductance	18 nH