

## NOT for Patient-Care Rooms - UL1363 Hospital-Grade Surge Protector with 6 Hospital-Grade Outlets, 6 ft. (1.83 m) Cord, 1050 Joules

MODEL NUMBER: SPS606HGRA



### Highlights

- 6 hospital-grade outlets
- 1050 joule rating
- 6-ft. cord with molded right angle hospital-grade plug
- All metal housing

### Package Includes

- SPS606HGRA Surge Suppressor
- Instruction manual with warranty information

Need to use a surge suppressor behind a desk or in a confined spot? The SPS606HGRA provides surge suppression with the convenience of a space-saving, right-angle hospital-grade plug for placing the units in confined areas and keyhole mounting tabs and flanges for easy installation.

### Features

- 1050-joule AC surge suppression rating
- Rugged all-metal housing withstands years of use without loss of ground path continuity
- 6 NEMA5-15R Hospital-Grade AC outlets
- 6-ft. AC cord with integrated, molded Hospital-Grade NEMA 5-15PHG plug
- Keyhole mounting tabs and flanges
- Switch safety cover prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120 volt, 50/60Hz electrical compatibility
- Certified by UL (USA) and cUL (Canada)
- UL1449 3rd Edition listed
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required

## Specifications



|  |   |
|--|---|
| UPC Code                                     | 037332167088                                |
| <b>INPUT</b>                                 |   |
| Nominal Input Voltage(s) Supported           | 120V AC                                     |
| Recommended Electrical Service               | 120V (110-125V)                             |
| Voltage Compatibility (VAC)                  | 120   |
| Maximum Surge Amps                           | 19500                                       |
| Input Plug Type                              | NEMA 5-15P-HG                               |
| Input Cord Length (ft.)                      | 6   |
| Right-Angle Plug                             | Yes   |
| Input Cord Length (m)                        | 1.83  |
| Integrated Cord Clip                         | No  |
| <b>OUTPUT</b>                                |   |
| Frequency Compatibility                      | 50 / 60 Hz                                  |
| Output (Watts)                               | 1800  |
| Output Receptacles                           | (6) 5-15R-HG                                |
| Circuit Breaker (amps)                       | 15  |
| Transformer Accommodation                    | (2) Yes                                     |
| Right-Angle Outlets                          | No  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |   |
| Diagnostic LED(s)                            | Yes   |
| Diagnostic LED Details                       | LINE POWER PRESENT (green)                  |
| Locking Switch Cover                         | Locking switch cover                        |
| <b>SURGE / NOISE SUPPRESSION</b>             |   |
| AC Suppression Joule Rating                  | 1050  |
| AC Suppression Response Time                 | < 1 ns                                      |
| Protection Modes                             | Includes full normal mode surge suppression |
| Clamping Voltage (RMS)                       | 140   |
| Automatic Shut-Off                           | Yes   |
| <b>DATALINE SURGE SUPPRESSION</b>            |   |
| Telephone/DSL Protection                     | No  |
| Cable (Coax) Protection                      | No  |
| Network (Ethernet) Protection                | No  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

| <b>PHYSICAL</b>                     |   |
|-------------------------------------|---|
| Color                               | White   |
| Antimicrobial Coating               | No  |
| Color (AC Line Cord)                | Light Gray                                      |
| Integrated Keyhole Mounting Slots   | Yes   |
| Material of Construction            | Metal   |
| Receptacle Color                    | White   |
| Shipping Dimensions (hwd / cm)      | 5.59 x 37.85 x 17.02                            |
| Shipping Dimensions (hwd / in.)     | 2.20 x 14.90 x 6.70                             |
| Shipping Weight (kg)                | 1.09  |
| Shipping Weight (lbs.)              | 2.40  |
| Unit Dimensions (hwd / cm)          | 3.81 x 34.9 x 6.35                              |
| Unit Dimensions (hwd / in.)         | 1.5 x 13.75 x 2.5                               |
| Unit Weight (kg)                    | 1.45  |
| Unit Weight (lbs.)                  | 3.20  |
| <b>SPECIAL FEATURES</b>             |   |
| Rotatable Outlets                   | No  |
| <b>STANDARDS &amp; COMPLIANCE</b>   |   |
| Canada                              | cUL (Series Number: AGIB12015SL)                |
| UL1449 3rd Edition (AC Suppression) | UL1449 3rd Edition (Series Number: AGIB12015SL) |
| UL1363 (Power Tap)                  | UL1363 (Series Number: AGIB12015SL)             |
| <b>WARRANTY</b>                     |   |
| Product Warranty Period (Worldwide) | Lifetime limited warranty                       |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>