

Product data sheet

Characteristics

SSP04XDSE15A

Surge protection device, XDSE, 150kA,
480Y/277 VAC, 3 phase, 4 wire, SPD type 2



Main

Product	Surge protection device
---------	-------------------------

Complementary

Surge Current	150 A per phase
Voltage Rating	480Y/277 V AC
Number of Phases	3 phase
Wiring Configuration	4-wire
MCOV	320 V
Rated Current	20 kA
Input voltage	1200 V L-N 1200 V L - G 1200 V L - L 2000 V N - G
Height	5.98 in (152 mm)
Width	5.98 in (152 mm)
Depth	3.98 in (101 mm)

Environment

Enclosure Rating	NEMA 4X
------------------	---------

Ordering and shipping details

Category	08466-SURGE PROTECTION HWA
Discount Schedule	DE1B
GTIN	785901085089
Nbr. of units in pkg.	1
Package weight(Lbs)	3.91 lb(US) (1.774 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.98 in (15.2 cm)
Package 1 width	5.98 in (15.2 cm)
Package 1 Length	3.98 in (10.1 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration