

NOTES:


| MATERIAL: HOUSING: SHELL: CONTACT: | THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED |
|--|--|
| OPERATING TEMPERATURE: | -55°C ~ 125°C |
| POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING SIGNAL CONTACT RESISTANCE: | 50Ω (IMPEDANCE) : 5A PER CONTACT 10mΩ MAX. |
| INSULATOR RESISTANCE: DIELECTRIC | 5000MΩ min. |

WITHSTANDING VOLTAGE:


.XX ±0.13

.XXX ±0.05

1000V AC rms



| | | | SW REFERENCE NO.: 630 COMBO ASSEMBLY | | |
|--|--|-------------------------|--------------------------------------|-------|--|
| COMBINATION D-SUB | | DRAWN: C.B | DATE: JAN. 01/20 | 19 | |
| | | CHECKED: | DATE: | | |
| EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE | C THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC. AND | SCALE: (IN C.A.D. 1:1) | SHEET 1 OF | 2 | |
| | | DRAWING NUMBER: 630-5W5 | -240-5TC | ISSUE | |
| | MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | PART NUMBER: 630-5W5 | -240-5TC | 1 | |





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

