


VC0805K121R030

VC, Varistors, Low Voltage, 38 V, 30 VAC, 47 V, 77 V, 1 A, 120 A, 200 mJ, 5000 uW



Click here for the 3D model.

Dimensions	
Chip Size	0805
L	2mm +/-0.25mm
W	1.25mm +/-0.2mm
Т	1.05mm MAX
В	0.5mm +/-0.25mm

Packaging Specifications	
Packaging	T&R
Packaging Quantity	3500

General Information		
Series	VC	
Туре	Varistors	
Style	SMD Chip	
Description	Surface Mount Varistors	
Features	Low Voltage	
Termination	Nickel Tin	
RoHS	Yes	
Qualifications	IEC, UL, AEC-Q200	
AEC-Q200	Yes	

Specifications	
Voltage DC	38 VDC (25C)
Voltage AC	30 VAC
Temperature Range	-55/+125°C
Storage Temperature Range	-55/+150°C
Varistor Voltage	47 VDC at 1 mA
Clamping Voltage	77 V
Clamping Current	1A (8/20 us MAX)
Surge Current	120 A (8/20 us MAX)
Energy	0.2 J (10/1000 us MAX)
Capacitance	230 pF (1kHz)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.