XESP2051

Limit switch contact block, Limit switches XC Standard, XESP, 1C/O snap action, simultaneous, silver plated





Main

Mairi	
Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch contact block
Device short name	XESP
Number of poles	1
Contact operation	Snap action, simultaneous
Contacts type and composition	1 C/O

Complementary

- Comprehensive	
Electrical connection	Screw-clamp terminals 1 x 0.752 x 1.5 mm ²
Contacts insulation form	Za
Contacts material	Silver plated contacts
Positive opening	Without
Minimum actuation speed	0.01 mm/s
Maximum resistance across terminals	25 mOhm IEC 60255-7 category 3
Electrical durability 5000000 Cycles, DC-13 120 V, 4 W 60 cyc/mn 0.5 IEC 60947-5000000 Cycles, DC-13 24 V, 10 W 60 cyc/mn 0.5 IEC 60947-5000000 cycles, DC-13 48 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-	

Ordering and shipping details

Category	22449 - LIMIT SWITCHES, ACCESSORIES	
Discount Schedule	Т	
GTIN	3389110645743	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.74 oz (21 g)	
Returnability	Yes	
Country of origin	ID	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	0.98 in (2.5 cm)	
Package 1 width	2.76 in (7 cm)	
Package 1 Length	2.76 in (7 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65 WARNING: This product can expose you to chemicals incl phthalate (DINP), which is known to the State of California and Di-isodecyl phthalate (DIDP), which is known to the St to cause birth defects or other reproductive harm. For more www.P65Warnings.ca.gov		
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free	Yes	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

	·
Marranti	10 months
vvarranty	18 months
•	