SIEMENS

Data sheet

3SU1001-0AA70-0AA0-Z Y11



Illuminated pushbutton, 22 mm, round, plastic, clear, pushbutton, flat, latching, Push-to-release mechanism, with laser labeling, upper case

product brand name	SIRIUS ACT			
product designation	Illuminated pushbuttons			
design of the product	Actuating/signaling element			
product type designation	3SU1			
product line	Plastic, black, 22 mm			
Enclosure				
number of command points	1			
Actuator				
design of the actuating element	Flat button			
principle of operation of the actuating element	latching			
product extension optional				
light source	Yes			
contact module	Yes			
color of the actuating element	clear			
material of the actuating element	plastic			
shape of the actuating element	round			
outer diameter of the actuating element	29.5 mm			
marking of the actuating element	Any inscription, text in upper case			
type of unlocking device	push-to-unlatch mechanism			
Front ring				
product component front ring	Yes			
design of the front ring	Standard			
material of the front ring	plastic			
color of the front ring	black			
General technical data				
protection class IP	IP66, IP67, IP69(IP69K)			
degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13			
shock resistance				
• acc. to IEC 60068-2-27	Sinusoidal half-wave 50g / 11 ms			
 for railway applications acc. to DIN EN 61373 	Category 1, Class B			
vibration resistance				
• acc. to IEC 60068-2-6	10 500 Hz: 5g			
 for railway applications acc. to DIN EN 61373 	Category 1, Class B			
operating frequency maximum	1 800 1/h			
mechanical service life (switching cycles) typical	500 000			
reference code acc. to IEC 81346-2	S			
Ambient conditions				

-25 ... +70 °C • ambient temperature during operation -40 ... +80 °C

• ambient temperature during storage

environmental category during operation acc. to IEC

3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95 %)

607	21		

Installation/ mounting/ dimensions		
height	29.5 mm	
width	29.5 mm	
shape of the installation opening	round	
mounting diameter	22.3 mm	
positive tolerance of installation diameter	0.4 mm	
mounting height	11 mm	
installation width	29.5 mm	
installation depth	24.3 mm	
Certificates/ approvals		

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1001-0AA70-0AA0-Z Y11

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1001-0AA70-0AA0-Z Y11

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1001-0AA70-0AA0-Z Y11

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1001-0AA70-0AA0-Z Y11&lang=en

last modified:

1/18/2021 🖸