

## Specification Sheet

Part Number: 596-00673



Solar Label, Reflective, CAUTION SOLAR CIRCUIT, 6.5" x 1.0", V, Yellow, 10/pkg

<b>Article Number</b>	596-00673
<b>Type</b>	CSCIRLBL10
<b>Color</b>	Yellow (YE)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>•Made with UV-stable inks and materials for durability and weather resistance.</li><li>•Reflective properties to meet applicable NEC code requirements for reflective identification.</li><li>•Supplied with an aggressive adhesive to ensure long life.</li><li>•Meets NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.</li></ul>
<b>Quantity Per</b>	pack

**Product Description**

HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC 2014, 2017 and 2020 code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC 2014, 2017 and 2020 code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack.

**Short Description**

Solar Label, Reflective, CAUTION SOLAR CIRCUIT, 6.5" x 1.0", V, Yellow, 10/pkg

**Global Part Name**

CSCIRLBL10-505/281-YE

**Technical Description**

Solar Label, Caution - Solar Circuit Reflective Label, 6.5" X 1.0", Yellow

**Local Order Number 2**

Cross Reference = 50 per roll: 596-00615

**Width W (Imperial)**

6.5

**Width W (Metric)**

165.1

**Thickness T (Imperial)**

0.0025

**Thickness T (Metric)**

64.0

**Height H (Imperial)**

1.0

**Height H (Metric)**

25.40

**Material**

Type 505/281, UV Stable Reflective Vinyl with Clear Polyester Laminate

**Material Shortcut** 505/281

**Adhesive** Acrylic

**Halogen free** No

**Adhesive Operating Temperature** -40°F to +174°F (-40°C to +79°C)

**Operating Temperature (Metric)** -40°F to +174°F (-40°C to +79°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Certification/Specification WEB** NEC2014

**Warranty (US)** Yes

**UL Recognized (US)** Yes

**Package Quantity(Imperial)** 10

**Package Quantity (Metric)** 10

**Customs Number** 3919905060

**Labels per Column** 1

**Labels per Row** 1

**Weight (Metric)** 0.521

**Weight (Imperial)** 1.14

---

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)