

Master cable - SAC-12P-10,0-PUR/M12FS MC - 1530799


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Master cable, 12-position, PUR/PVC, black RAL 9005, free cable end, on Socket straight M12, A-coded, cable length: 10 m



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 024471
GTIN	4046356024471

Technical data

General

Rated voltage	30 V AC
	30 V DC
Number of positions	12
Flammability rating according to UL 94	HB

Ambient conditions

Degree of protection	IP68
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)

Insulation material

Contact material	CuSn
Contact surface material	Au

Standards and Regulations

Standard designation	M12 connector
Standards/regulations	IEC 61076-2-101
Flammability rating according to UL 94	HB

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Master cable - SAC-12P-10,0-PUR/M12FS MC - 1530799

Technical data

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>