

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1720420508](#)
Status: **Active**
Overview: Super Sabre™ Connector System
Description: Super Sabre™ Vertical Header, 5 Circuit, Long Solder Tail with Board Lock

Documents:

[3D Model](#) [Product Specification PS-171825-001 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA LR19980
 UL E29179

General

Product Family PCB Headers
 Series [172042](#)
 Application Power, Signal, Wire-to-Board
 Comments Operating Temperature Per USCAR-2; Class 3
 Overview [Super Sabre™ Connector System](#)
 Product Name Super Sabre™
 UPC 887191565323

Physical

Breakaway No
 Circuits (Loaded) 5
 Circuits (maximum) 5
 Color - Resin Black
 Durability (mating cycles max) 25
 First Mate / Last Break No
 Flammability 94V-0
 Glow-Wire Compliant Yes
 Lock to Mating Part Yes
 Material - Metal Copper
 Material - Plating Mating Silver
 Material - Plating Termination Matte Tin, Nickel
 Material - Resin High Temperature Thermoplastic
 Net Weight 6.405/g
 Number of Rows 1
 Orientation Vertical
 PC Tail Length 5.33mm
 PCB Retention Yes
 Packaging Type Tray
 Pitch - Mating Interface 7.50mm
 Plating min - Mating 0.025µm
 Plating min - Termination 0.025µm
 Polarized to Mating Part Yes
 Surface Mount Compatible (SMC) Yes
 Temperature Range - Operating -40°C to +125°C
 Termination Interface: Style Through Hole

Electrical

Current - Maximum per Contact 30.0A per blade
 Voltage - Maximum 600V AC (RMS)

Solder Process Data

Duration at Max. Process Temperature (seconds) 030
 Lead-free Process Capability SMC&WAVE
 Max. Cycles at Max. Process Temperature 003



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per
 -ED/79/2015 (17
 December 2015)

Halogen-Free

Status

Low-Halogen

**Need more information on product
 environmental compliance?**

Email productcompliance@molex.com
 Please visit the [Contact Us](#) section for any
 non-product compliance questions.

China ROHS

ELV

Green Image

Not Relevant

Search Parts in this Series

[172042](#) Series

Mates With

[172672](#) Crimp Housing

Process Temperature max. C 260

Material Info

Reference - Drawing Numbers

Product Specification PS-171825-001
Sales Drawing SD-172042-001

This document was generated on 02/05/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION