

Specification Sheet

Part Number: 596-00832

Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure.

Aggressive adhesive ensures strong bond, even on powder coated surfaces.

TURN OFF PHOTOVOLTAIC AC DISCONNECT PRIOR TO

WORKING INSIDE PANEL

Meets or exceeds NEC & IFC standards for printed text, character height, color and outdoor UV stability.

Optional Paint Shields provide additional protection for pre-printed and variable data placards.

Metal Solar Placard, WARNING TURN OFF PHOTOVOLTAIC..., 3.75"x2", AA, Orange/Silver, 5/pkg

Article Number 596-00832

Type WTOPVLBLM5

Color Orange (OG)

Quantity Per pack

_				-	_							
ם	rn	~ I	114	rt.	- 11	es	r	rı	n	tı	\mathbf{a}	'n
	v	u	и١	Ŀι	$\boldsymbol{\omega}$	CO	u		v	LI	u	

Metal Solar Placards offer maximum durability and ease in code compliance. Perfect for solar applications, a special process seals metallic particles under a clear anodized layer, which results in markings that have been tested and rated to last up to 25 years in outdoor use, even in direct sunlight. Markers are designed to meet the latest National Electrical Code (NEC 2014), with pre-printed warning or caution messaging that conforms to Article 690, as well as ANSI guidelines. Pre-printed placards may be more acceptable to some local Authorities Having Jurisdiction (AHJs), who may have a preference for placard-style identification.

Short Description

Metal Solar Placard, WARNING TURN OFF PHOTOVOLTAIC..., 3.75"x2", AA, Orange/Silver, 5/pkg

Global Part Name

WTOPVLBLM5-AA-OG

Technical Description

3.75" X 2" Black text on an Orange/Silver Aluminum background that reads as: "WARNING TURN OFF PHOTOVOLTAIC AC DISCONNECT PRIOR TO WORKING INSIDE PANEL." - 5 per pack.

Local Order Number 2

Cross Reference = Paint Shield: 596-00793

Length L (Imperial)

3.75

Length L (Metric)

95.25

Width W (Imperial)

3.75

Width W (Metric)

95.25

Height H (Imperial)

2.0

Height H (Metric)

50.80

Material

Anodized Aluminum (AA)

Material Shortcut

AA

Adhesive

Ultra High Bond Permanent Acrylic Adhesive

Halogen Free

No

Adhesive Operating Temperature

from +50°F (from +10°C)

Operating Temperature

-40°F to +203°F (-40°C to +95°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant

Yes

Certification/Specification

NEC2017

Warranty (US)

Yes

Package Quantity (Imperial)

5

Package Quantity (Metric)

5

Customs Number

7616995195

Labels per Column

1

Labels per Row

1

© 2021 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions