

A72PQ2680AA00K

Aliases (72PQ2680AA00K)

A72, Film, Film/Foil Polypropylene, General Purpose, 0.068 uF, 10%, 300 VAC, 630 VDC, 85°C

SIDE VIEW



Click here for the 3D model.

Dimensions	
D	11.5mm MAX
L	28mm MAX
НО	18.5mm +/-0.5mm
F	0.8mm +/-0.05mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	300

General Information		
Series	A72	
Dielectric	Film/Foil Polypropylene	
Style	Axial	
RoHS	Yes	
Lead	Wire Leads	
AEC-Q200	No	
Component Weight	3.6 g	
Miscellaneous	Above 85C DC And AC Voltage Derating Is 1.25%/C. maxK0 = 3300000.	

Specifications	
Capacitance	0.068 uF
Capacitance Tolerance	10%
Voltage AC	300 VAC
Voltage DC	630 VDC, 472.5 VDC (105C)
Temperature Range	-55/+105°C
Rated Temperature	85°C
Dissipation Factor	0.05% 10kHz, 0.1% 100kHz
Insulation Resistance	100 GOhms
Max dV/dt	2600 V/us
Inductance	28 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.