


R73QI2150SE30J

Aliases (73QI2150SE30J)

R73, Film, Film/Foil Polypropylene, Automotive Grade, 0.015 uF, 5%, 1000 VDC, 85°C, Lead Spacing = 15mm



Click here for the 3D model.

| Dimensions | |
|------------|--------------------|
| L | 18mm +/-0.5mm |
| н | 13.5mm +0.1/-0.5mm |
| Т | 7.5mm +0.2/-0.5mm |
| S | 15mm +/-0.4mm |
| LL | 4mm +2mm |
| F | 0.8mm +/-0.05mm |

Packaging Specifications

| Packaging | Bulk, Bag |
|--------------------|-----------|
| Packaging Quantity | 1000 |

| General Information | |
|---------------------|--|
| Series | R73 |
| Dielectric | Film/Foil Polypropylene |
| Style | Radial |
| Features | Automotive Grade, Pulse |
| RoHS | Yes |
| Lead | Cut |
| Qualifications | AEC-Q200 |
| AEC-Q200 | Yes |
| Component Weight | 2.3 g |
| Miscellaneous | Above 85C DC And AC Voltage Derating Is 1.25%/C. |

| Specifications | | |
|---------------------------|--------------------------------------|--|
| Capacitance | 0.015 uF | |
| Capacitance Tolerance | 5% | |
| Voltage AC | 400 VAC | |
| Voltage DC | 1000 VDC | |
| Temperature Range | -55/+105°C | |
| Rated Temperature | 85°C | |
| Dissipation Factor | 0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz | |
| Insulation Resistance | 100 GOhms | |
| Max dV/dt | 28000 V/us | |
| Inductance | 10 nH | |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.