


## NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, 30µ" GOLD PLATED



OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	50Ω (IMPEDAN
SIGNAL CONTACT CURRENT RATING:	5A PER CONTA


.X ±0.25 .XX ±0.13 .XXX ±0.05

**INSULATOR RESISTANCE:** DIELECTRIC WITHSTANDING VOLTAGE: Ω (IMPEDANCE)

PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX.

5000MΩ min.

1000V AC rms



	COMBINATION D-SUB		SW REFERENCE NO.: 629 COMBO ASSEMBLY				
			DRAWN: C.B		DATE: JAN. 01/2019		
			CHECKED:		DATE:		
		EDAC INC TORONTO, ONTARIO CANADA O QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C	C.A.D. 1:1)	SHEET 1 O	- 2
				DRAWING NUMBER: 629-36W		640-5TB	ISSUE
YOUR CONNECTION TO	YOUR CONNECTION TO QU			PART NUMBER	R: 629-36W4	640-5TB	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

