



**CONFIDENTIAL & PROPRIETARY INFORMATION**

This document contains Confidential and Proprietary Information of Alliance LLC, and all design, manufacturing, reproduction, use, and sale rights of such information are expressly reserved

ALL DIMENSIONS ARE IN MM (INCH)



**NOTES:**

- MAGNET PROPERTIES PER N-35SH:  
 Br: 11,800-12,200 G  
 Hc: 10,800-11,500 Oe  
 Hci: ≥20,000 Oe  
 T max: 150 C
- SUPPLIED MAGNETIZED THROUGH THE THICKNESS
- PARTS ARE NICKEL PLATED



REV	DESCRIPTION	DATE	BY

**TOLERANCES**  
(UNLESS OTHERWISE NOTED)

DECIMAL      METRIC  
 X.XX = ± .01    X.X = ± .25  
 X.XXX = ± .005   X.XX = ± .13

**ANGLES**  
 ± .5°

DO NOT SCALE DRAWING

<b>Alliance LLC</b>		
1450 CLARK DRIVE, VALPARAISO, INDIANA 46385		
DESCRIPTION: 5.0 mm x 4.0 mm DISC MAGNET		
<b>SENSOR MAGNET</b>		<b>P/N: ALC4044</b>
GRADE: N-35SH	Drwg by: BT	REV LEVEL: A
COATING: Nickel	Appr by: DV	Approval: 06-15-2017