

## ATGBICS Dell 470-ACEU Compatible SFP28 Direct Attach Copper Twinax Cable 25G SFP28 3m Passive

Brand : ATGBICS Product code: 470-ACEU-C

**Product name :** Dell 470-ACEU Compatible SFP28 Direct Attach Copper Twinax Cable 25G SFP28 3m Passive

Dell 470-ACEU Compatible SFP28 Direct Attach Copper Twinax Cable 25G SFP28 3m Passive

ATGBICS Dell 470-ACEU Compatible SFP28 Direct Attach Copper Twinax Cable 25G SFP28 3m Passive:

ATGBICS 470-ACEU compatible 25GBase-CU SFP28 to SFP28 direct attach cable operates over passive copper with a cable length of 3m. It is suitable for short reach connection between two SFP28 ports in 25G interconnecting networking applications. Our product is built to the exact specification of Dell 470-ACEU= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; SFF-8402 and SFF-8432 and MSA SFP+ MSA SFF-8431.

ATGBICS Dell 470-ACEU Compatible SFP28 Direct Attach Copper Twinax Cable 25G SFP28 3m Passive. Cable length: 3 m, Connector 1: SFP28, Connector 2: SFP28, Data transfer rate: 25000 Mbit/s







| Features  |  | Features   |                                      |
|---|--|--|--------------------------------------|
| Product colour * Cable length *   | le length * 3 m nector 1 * SFP28 nector 2 * SFP28 nector 1 gender * Male nector 2 gender * Male et material Polyvinyl chloride (PVC) ductor material Copper ernet interface type 25 Gigabit Ethernet lete 802.3by G wire size 30 | Plug and Play<br>Certification   | <b>√</b><br>CE,FCC                   |
| Connector 2 * Connector 1 gender * Connector 2 gender * lacket material |  | Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) | 0 - 70 °C<br>-40 - 80 °C<br>10 - 90% |
| Conductor material Ethernet interface type Networking standards         |  | Storage relative humidity (H-H)  Packaging data  Quantity per pack   | 10 - 85%<br>1 pc(s)                  |
| AWG wire size Data transfer rate  |  | <b>Technical details</b> Sustainability certificates   | RoHS                                 |



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.