


C440C103K1G5TA

General Information

AxiMax 400 Comm COG, Ceramic, 0.01 uF, 10%, 100 VDC, COG, AxiMax, Commercial Standard



Series AxiMax 400 Comm COG

Description AxiMax, Commercial Standard

RoHS Yes

Termination Tin

AEC-Q200 No

Halogen Free Yes

Click here for the 3D model.

Packaging Quantity

Dimensions	
D	3.81mm MAX
L	6.6mm MAX
LL	25.4mm MIN
F	0.51mm +0.025/-0.076mm

F	0.51mm +0.025/-0.076	5mm		
Packaging Specifications				
Packagir	ng	Bulk, Bag		

200

Specifications	
Capacitance	0.01 uF
Measurement Condition	1 MHz 1.0Vrms
Capacitance Tolerance	10%
Voltage DC	100 VDC
Dielectric Withstanding Voltage	250 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	COG
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	30PPM/C, 1kHz 1.0Vrms
Dissipation Factor	0.1% 1 MHz 1.0Vrms
Aging Rate	0% Loss/Decade Hour
Insulation Resistance	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.