




LA45-M6-PF

Ruland Adjustable Clamping Lever, Lever Length 45mm, Tapped Hole M6, Plastic Lever, Steel Inserts



Description

Ruland LA45-M6-PF is an adjustable clamping handle with a 45mm handle, M6 tapped hole, 10mm insert diameter, and 35mm overall height. The handle is plastic and the inserts are steel with a black oxide finish for reduced weight and easier adjustment of the handle in light duty applications. LA45-M6-PF is commonly found in packaging, printing, food processing, and medical systems where conveyor rails, sensors, screens, and other components require frequent adjustments without the use of tools. The adjustable feature of this handle allows it to be used in confined spaces with limited hand access or where 360 degree rotation is not possible. Serrations connect the insert to the handle for easy disengagement. The user pulls the handle upwards by hand to disengage the serrations allowing it to be swiveled to the desired clamping position. Serrations automatically re-engage once the user releases the handle locking it in-place. A M6 tapped hole is designed to mate with an equivalently sized threaded stud or rod for a quick installation. LA45-M6-PF is black to seamlessly integrate with the aesthetics of most equipment. It is manufactured by JW Winco, stocked by Ruland, and RoHS3 and REACH compliant.

Product Specifications

Thread (TH)	M6	Lever Length L1	45 mm
Overall Height H1	35 mm	Hub Height H2	24.5 mm
Hub Diameter DH	14.5 mm	Handle Disengagement Travel H3	3.5 mm
Thread Depth T	9 mm	Thread Pitch	1 mm
Sleeve Length L2	4 mm	Sleeve Diameter D1	10 mm
Handle Material	Plastic	Handle Color	Black
Insert and Screw Material	Steel	Insert and Screw Finish	Black Oxide
Weight (lbs)	0.032000	Manufacturer	JW Winco/ Otto Ganter
UPC	634529237427	Country of Origin	USA
Tariff Code	3926.90.2500	UNSPC	31162807

Prop 65  **WARNING** This product can expose you to the chemicals Nickel (metallic) and Lead, known to the State of California to cause cancer and reproductive harm. For more information go to www.P65Warnings.ca.gov.