



CORE DIMENSIONS		35T0119-00P			
UNCOATED CORE					
		MM	INCHES	MM	INCHES
OD	3.05	(.120)	±	.13	(.005)
ID	1.27	(.050)	±	.13	(.005)
TH	1.27	(.050)	±	.13	(.005)
SINGLE PARYLENE COATING		35T0119-00P			
OD	3.07	(.121)	±	.13	(.005)
ID	1.24	(.049)	±	.13	(.005)
TH	1.30	(.051)	±	.13	(.005)

WEIGHT / K 0.08 LBS  
 INITIAL PERMEABILITY 5000

ELECTRICAL SPECIFICATION								
	MIN (μH)	MIN TOL. (-20%)	NOM (μH)	MAX (μH)	MAX TOL. (+20%)	FREQ. (kHz)	VOLT. (V)	URNS
L	.889		1.112	1.334		100	≤ .00021	1
Q	10		-	-		100	≤ .00021	1

COATING SPECIFICATIONS			
TYPE	Max. Coating (mils.)	Min. DLB VAC	TEST FORCE (LB)
PARYLENE	0.5	1000	.09

NOTES:

- Cosmetic Specification refer to WI-QA-015.



Rev	Description	Date	INT
A	Original Draft	1995/6/7	JBE
B	REVISED PRINT	1995/6/7	JBE
C	UPDATED TO NEW FORMAT	1995/6/7	JBE
D	TRANSFER TO LOTUS NOTES	1997/10/21	TPM
E	ADDED PARYLENE D	1998/9/2	TPM
F	REMOVE D AND Q COATING SPECS CHANGE PART NUMBER AND REACTIVATE PRINT	2005/10/4	JRK
G	Revised Template	2006/6/1	WMM
H	Revised Template	2019/3/10	Jcai

Date: 2019/3/10	DWG # 35T0119-00P-H	Rev:
Drawn By: Jcai	Title # 35T0119-00P	H

Laird This document contains information which is proprietary to laird. No production or publication of this document in whole or in part shall be made without written authorization from Laird.