


THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

COMPLIANT





| Ν | O. | ΤI | E | S | 1 |
|---|----|----|---|---|---|
| | | | | | |


| MATERIAL: | |
|-----------|--|
| HOUSING: | |
| SHELL: | |
| CONTACT: | |
| | |

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ GOLD PLATED

OPERATING TEMPERATURE:

POWER/CO-AX CONTACT RATING:10A (CURRENT)(IF PRESENT)SIGNAL CONTACT CURRENT RATING:5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.INSULATOR RESISTANCE:5000MΩ min.

DIELECTRIC WITHSTANDING VOLTAGE:



| | SW REFERENCE NO.: 630 COMBO ASSEMBLY | | | |
|---------------------------------------|--|-------------------------|------------|-------|
| COMBINATION | DRAWN: C.B | DATE: JAN. 01/2019 | | |
| | CHECKED: | DATE: | | |
| EDAC INC | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC., AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1) | SHEET 1 OF | 2 |
| EDACINC TORONTO, ONTARIO CANADA | | DRAWING NUMBER: 630-2WK | 2650-1NB | ISSUE |
| YOUR CONNECTION TO QUALITY & SERVICE | | PART NUMBER: 630-2WK | 2650-1NB | 1 |

-55°C ~ 125°C

1000V AC rms

