


TOLERANCE UNLESS OTHERWISE SPECIFIED				
.X	±0.25			
.XX	±0.13			
.XXX	±0.05			

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER ORIGINAL



NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, TIN PLATED

CONTACT: COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE: -55°C ~ 125°C

POWER/CO-AX CONTACT RATING: 20A (CURRENT)

(IF PRESENT)


SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT

SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: 5000MΩ min.

DIELECTRIC

WITHSTANDING VOLTAGE: 1000V AC rms



COMBINATION D-SUB



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

SW REFERENCE NO.: 630 COMBO ASSEMBLY				
	DRAWN: C.B	DATE: JAN. 01/2019		
	CHECKED:	DATE:		
	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF 2		
	DRAWING NUMBER COO EME OFO OTA			

DRAWING NUMBER: 630-5W5-250-2T1 ISSUE PART NUMBER: 630-5W5-250-2T1



20.33

TOLERANCE UNLESS OTHERWISE SPECIFIED

.X ±0.25 .XX ±0.13 .XXX ±0.05

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER (1) **ORIGINAL**

00 2W2

2WK2

o€:

5W1

00000 3W3

0000) 3WK3

0...0 7W2

...0... 11W1

00000 5W5

9W4

000::::0

13W3

0...... 17W2

..... 21W1

000000:::

000:::::000

17W5

00000000 8W8

000:::::0 25W3

13W6

O :::::::::::: O 27W2

00*******00

21W4

00000000 24W7

36W4





47W1

COMBINATION D-SUB

YOUR CONNECTION TO QUALITY & SERVICE

EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

	SW REFERENCE NO.: 630 COMBO ASSEMBLY						
	DRAWN: C.B		DATE: JAN. 01/2019			19	
	CHECKED:		DATE:				
	SCALE: N.T.S		SHEET	2	OF	2	
'	DRAWING NUMBER: 630-5W5-250-2T1		Ī	ISSUE			

630-5W5-250-2T1

PART NUMBER: