	- m		0	₩	A
	Keying Shown as example		LAYOUT SHOWN AS	EXAMPLE	
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal				
-Shell Material: Composite-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer	ØS25 MaxZ'31.5 MaxVV THREADM15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)		
-Contact Plating       : Gold over copper Alloy 0.8μm minimum         -Durability       : 500 Mating cycles         Delivered with Sourieu contacts and Accessories			PN: 8D511M35SE		
-Delivered with Souriau contacts and Accessories -Temperature Range <u>-</u> -65°C to +200°C			A 17-10-2016 First Release		
-Salt Spray : 2000 hours		A 17-10-2016	Latest modification - by		MOD N°
Mass : 16 g ± 10%		Designed By:	Date:	CUSTOMER DRA	
		TITLE Composite Plug 8D series			
BASIC SERIES: 8D 5 - 11 M SHELL TYPE : Plug with RFI Shielding	35 S E	SCALE NA	General linear Tolerances: ±	NPRDS / PROJ 859	ECT
	ORIENTATION : E	SOURIAU	This document is the property of		
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	CONTACT TYPE : SOCKET(500 Matings)			COMMUNICATED V	without permission
CONTACT TYPE       : Standard Crimp Contact         SHELL SIZE       : 11         PLATING       : M = Nickel	CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 11-35	FORMAT A3	SOURIA	U DRG N°	SHEET

	<b>工</b>	۵	н гт	m	D	0
		Contact Layout				
4	-x	$ \begin{array}{c} & & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & $				
	2 +.085 (2.16) 3 +.138 (3.51) 4 +.138 (3.51) 5 +.086 (2.16) 6 +.000 (0.00)	Contacts (Insert arrangement 11-35)           Orn         Contact position ID         X-axis (mm)         Y-axis (mm)           (mm)         -0.38 (3.51)         -0.45 (1.14)           +.146 (3.71)         8        138 (3.51)         -0.45 (1.14)           +.146 (3.00)         9        138 (3.51)         +.045 (1.14)          045 (1.14)         10        085 (2.16)         +.118 (3.00)          045 (1.14)         11         +.000 (0.00)         +.056 (1.42)          118 (3.00)         12         +.049 (1.24)        035 (0.89)          118 (3.00)         -         -         -				
	Shell Arrangement Nu size no. c	Applicable to MIL-DTL-38999 only)           umber of         Size         Service         Contact         Supersedes           ontacts         contacts         rating         location         13         22D         M         All         MS27526-35				
ယ						
						SOURIAU shall not be liable for a due to a use of the Products the Specifications issued by either (professional recommend
N						Cour
						PN: 8D511
					A 17-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:
					TITLE	Comp
-					SCALE	General linear Tolerances:
					SOURIA	U WWW.SOURIAU.
					FORMAT A3	SOURIA 8D511
	Н	G	F	E	D	C

