ב בר	т п		0	₿ >		]	
						4	
<u>م</u>	I		LAYOUT SHOWN AS EXA	MPLE		3	
	Keying Shown as example						
CHARACTERISTICS	Connector dimension						
-Standard : Based on MIL-DTL-38999 Series III	DimNominalØS41.7 Max						
-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy	Z 31 Max VV THREAD M31x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Seals & Grommet : Silicon Elastomer			Country FR	Jurisdiction & Control List		2	
·Contact Plating       : Gold over copper Alloy 0.8μm minimum         ·Durability       : 500 Mating cycles			FR Not Listed PN: 8D521W41PNL				
-Delivered without Souriau contacts			PIN. 6D521004	THINT			
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 10-10-2016	First Release				
		ISS DATE	Latest modification - by		MOD N°	,	
		Designed By:	Date:	CUSTOMER DRAWING		_	
		TITLE	TITLE     Aluminium Plug 8D series				
→ BASIC SERIES: 8D 5 - 21 W SHELL TYPE : Plug with RFI Shielding	41 P N L Delivered W/O Contact	SCALE -	General linear Tolerances:	NPRDS / PROJECT <b>859</b>		_	
CONTACT TYPE : Standard Crimp Contact	ORIENTATION : N	<u> </u>	NA     Image: Source of the second seco			-	
SHELL SIZE : 21	CONTACT TYPE : PIN(500 Matings	- SUURIAU					
PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 21-4:	—	SOURIAU D		SHEET	_	
		- A3	8D521W41		1/2		
			020210013		1		

		۵	г П	m		0
		Contact Layout				
4		, *Y				
	<	31° 23 31° 23 31° 20 HOLES 10° 20 HOLES				
		635 D.A				
	Shell Arrangement Num size no. con	Insert arrangement 21-41 Iber of Size Service Contact Supersedes tacts contacts rating location	7			
ယ	21 -41 4	41 20 I All MS20055-41				
	1					
						SOURIAU shall not be liable for ar due to a use of the Products w
						the Specifications issued by either of (professional recommendation)
						Count
N						FR
						PN: 8D521V
						116 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumir
					SCALE	General linear Tolerances:
<b>→</b>					NA	
					SOURIA	U WWW.SOURIAU.0
					FORMAT A3	SOURIAU
l	Н	G	F	E		8D521W
					V	

