

DEUTSCH | DEUTSCH HD, DEUTSCH HDP

TE Internal #: HDP26-24-9PE

Housing for Male Terminals, Wire-to-Wire, 9 Position, Sealable,

Black, Wire & Cable, Power & Signal, Cable Mount (Free-Hanging),

Hybrid

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH HDP20 Housings



Connector & Housing Type: Housing for Male Terminals

Mating Pin Diameter: 2.39 mm, 3.61 mm, 5.72 mm [.094 in, .142 in, .225 in]

Connector System: Wire-to-Wire

Number of Positions: 9

Sealable: Yes

All DEUTSCH HDP20 Housings (324)

Features

Product Type Features

1 Toduct Type Teatures	
Connector Shape	Circular
Connector & Housing Type	Housing for Male Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	Yes
Primary Locking Feature	Contact Retainer
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Blank Cavity Position	0
Connector Seal Code	E Seal
Number of Positions	9
Electrical Characteristics	
Operating Voltage	250 VAC
Nominal Voltage Architecture	12 V, 24 V, 48 V
Body Features	
Cable Exit Angle	180°

Black

Primary Product Color



Contact Features

Contact Size	Size 12, Size 4, Size 8
Contact Type	Pin
Mating Pin Diameter	2.39 mm, 3.61 mm, 5.72 mm[.094 in][.142 in] [.225 in]
Contact Current Rating (Max)	25 A, 60 A, 100 A

Mechanical Attachment

Terminal Position Assurance	No
Strain Relief	Add By Accessory
Mating Alignment Type	Guide Slot
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material PA GF

Dimensions

Connector Height	49.53 mm[1.95 in]
Product Width	49.53 mm[1.95 in]
Product Length	38.63 mm[1.521 in]
Accepts Insulation Diameter Range	2.46 – 4.01 mm, 3.43 – 5.59 mm, 6.63 – 7.42 mm[.097 – .158 in][.135 – .22 in][.261 – .292 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

Degree of Protection	IP67
UL Flammability Rating	20mm Flame Test per Standard UL-94

Packaging Features

Packaging Method	Box	
------------------	-----	--

Other



Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2023 (233) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts













TE Part # 114008-ZZ EXT TOOL, SIZE 8, 8-10 AWG, N, GRN



TE Part # HD30-24BT BOOT, 24SZ, ST, GRY



TE Part # CAT-H3930-B128 DEUTSCH HD30 Backshells



TE Part # 114009-ZZ EXT TOOL, SIZE 4, 6 AWG, N, WHT



TE Part # HD30-24BT-BK BOOT, 24SZ, ST, BLK



TE Part # 1060-12-0144 PIN, SF, SIZE 12, 12-14, AU/SN



TE Part # 1060-12-0222 PIN, SF, SIZE 12, 10, NI/NI



TE Part # 1060-12-0166 PIN, SF, SIZE 12, 12-14, NI/SN



TE Part # HD30-24BT-90-BK BOOT, 24SZ, RA, BLK

TE Part # 1060-12-0244 PIN, SF, SIZE 12, 10, AU/SN

TE Part # MT-90BT-HT-24 BOOT, 24SZ, RA, HI TEMP, YEL TE Part # MT-90BT-HT-24BK BOOT, 24SZ, RA, HI TEMP, BLK

Also in the Series | DEUTSCH HD



Automotive Connector Caps & Covers




Automotive Housings(741)




Automotive Seals & Cavity Plugs(10)



Insertion & Extraction Tools(11)



Other Automotive Connector Accessories(11)



PCB Headers & Receptacles(1)

Also in the Series | DEUTSCH HDP





Automotive Connector Caps & Covers (12)




Automotive Housings(331)



Automotive Seals & Cavity Plugs(1)





Customers Also Bought



TE Part #HDP26-24-9SE-L017
DEUTSCH HDP20 Housings



TE Part #DT04-12PA-CL06 REC, 12P, BLK, E, FLANGE, A



TE Part #1011-331-0205 BKSHL, 2P, BLK, PLG, RA, NW 8.5/10



Documents

Product Drawings

PLG, 9P, BLK, E, 4/8/12, P

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_HDP26-24-9PE_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_HDP26-24-9PE_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_HDP26-24-9PE_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Housing for Male Terminals, Wire-to-Wire, 9 Position, Sealable, Black, Wire & Cable, Power & Signal, Cable Mount (Free-Hanging), Hybrid



Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English