

Specification Sheet

Part Number: 596-00664



Solar Label, Warning Turn off PV Prior to..., 4.12" x 2.0", V, Orange, 10/pkg

Article Number	596-00664
Type	WTOPVLBL10
Color	Orange (OG)
Features & Benefits	<ul style="list-style-type: none">• Made with UV-stable inks and materials for durability and weather resistance.• Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.• Abrasion resistant for high-performance identification.• Meets NEC and IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Quantity Per	pack

Product Description

HellermannTyton Pre-Printed Vinyl Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives designed to adhere to both baked enamel and powder coated surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Solar Label, Warning Turn off PV Prior to..., 4.12" x 2.0", V, Orange, 10/pkg

Global Part Name

WTOPVLBL10-443/281-OG

Technical Description

Solar Label, Warning - Turn Off PV Label, 4.12" X 2.0", Orange/White

Local Order Number 2

Cross Reference = 50 per roll: 596-00499; Metal Solar Placard 5 pack: 596-00832

Width W (Imperial)

4.1

Width W (Metric)

104.14

Thickness T (Imperial)

0.0025

Thickness T (Metric)

64.0

Height H (Imperial)

2.0

Height H (Metric)

50.80

Width of Liner (Metric)

107.69

Width of Liner (imperial)

4.24

Material	Type 443/281, UV Stable Flexible White Vinyl with Clear Polyester Laminate
Material Shortcut	443/281
Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature (Metric)	-40°F to +174°F (-40°C to +79°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	NEC2014 NEC2017 NEC2020 UL 969
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	10
Package Quantity (Metric)	10
Customs Number	3919905060
Labels per Column	1
Labels per Row	1
Weight (Metric)	0.104

Weight (Imperial)

0.23