

KEY-PLUG XM-400, removable data storage medium for activating Layer 3 features for SCALANCE XM-400 and for simple device replacement in case of fault, and for Recording of configuration data.



ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation during storage during transport 	0 ... 60 °C -40 ... +80 °C -40 ... +80 °C
relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	
width	24.3 mm
height	17 mm
depth	8.1 mm
net weight	5 g
design of the removable storage	
<ul style="list-style-type: none"> C-PLUG KEY-PLUG 	No Yes
product features, product functions, product components / general	
storage capacity	256 Mibyte
standards, specifications, approvals	
reference code	
<ul style="list-style-type: none"> according to IEC 81346-2:2019 	CFA
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> to website: TIA Selection Tool to web page: selection aid TIA Selection Tool to the website: IWLAN to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Selection guide for cables and connectors to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	http://www.siemens.com/tia-selection-tool http://www.siemens.com/snst http://www.siemens.com/iwlan http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter https://sie.ag/2QdlxcP http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
last modified:	5/20/2021