



Pin 1 ... 4: 0.75 mm²

1	brown	1
2	white	2
3	blue	3
4	black	4

Item description

Short description:

- PUR, halogen-free
- UL / CSA
- Suitable for drag chains
- Silicon- and CFC-free
- High resistance to microbes, hydrolysis, oil, chemicals and UV radiation
- High chemical resistance
- Cable used: UL listed

Subject to changes. Please also observe the further product documentation!

Data

Technical data

Connection type	M12 socket - M12 plug
Pole number	4
Cable connection direction to mating direction	90 °
Cable connection direction to mating direction (2)	90 °
Connector interface coding (cable/adapter) 1 1	A-coded
Connector interface coding (cable/adapter) 2 1	A-coded
Cable length	2.5 m
PLC manufacturer	WAGO
Operating voltage	250 VAC/DC
Operating current	4 A
Rated surge voltage	2.5 kV
Contact resistance	10 mΩ
Insulation resistance	1000 MΩ
Conductor resistance	≤ 26 Ω/km

Mechanical Data

Bending radius	10 x cable diameter (min.)
Bending cycles	4 Mio.
Drag chain capability	yes
Sheathed cable diameter	6 ... 6.4 mm
Type code	Lif9YH-11YH 4x0.75 mm ²
Conductor configuration	Bare copper wire (40 x 0.15 mm)
Conductor insulation	PP9Y (halogen-free)
Housing material	TPU/TPU, black (~ RAL 9005)
Tightening torque	1 Nm
Weight	173 g

Environmental requirements

Ambient (operating) temperature (dynamic)	-30 ... +80 °C
Ambient (operating) temperature (static)	-30 ... +80 °C
Protection type	IP67
Pollution degree	3/2 per IEC 60664-1

Subject to changes. Please also observe the further product documentation!

Commercial data

eCl@ss 10.0	27-06-18-01
eCl@ss 9.0	27-06-18-01
ETIM 8.0	EC001855
ETIM 7.0	EC003249
PU (SPU)	1 pcs
Packaging type	box
Country of origin	DE
GTIN	4050821082378
Customs tariff number	85444290900

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	f85aa57b-74c1-4d93-b7b3-977412a39fec
SCIP notification number (Belgium)	673a98c2-9f03-4e84-b4b2-c73b13e325c6
SCIP notification number (Bulgaria)	e602a346-8384-429b-b0f5-fb6c841fb57a
SCIP notification number (Czech Republic)	21148b64-0cea-4122-81c5-7dc6d7e89f94
SCIP notification number (Denmark)	f0574812-d296-4d11-be97-4c007d607a92
SCIP notification number (Finland)	7f6c4fab-9288-40a7-a6e6-940ffc50f7a1
SCIP notification number (France)	34bac5fb-4556-4387-95db-043b68763851
SCIP notification number (Germany)	e2d30d8c-1c1b-4548-a689-5edc962d3a9b
SCIP notification number (Hungary)	1abf0ab2-6275-48c2-b030-2256fddcc65d
SCIP notification number (Italy)	a4460bc4-8139-452a-a3f8-4a9d1f915069
SCIP notification number (Netherlands)	74c4887b-0f53-46ff-b7bb-b586f3d9f62f
SCIP notification number (Poland)	c0aa58a2-1ce7-40f1-a4aa-8a622963bf97
SCIP notification number (Romania)	597c593e-595c-4c59-b9b4-e5f6228df9f5
SCIP notification number (Sweden)	cdc0831d-a9b8-4b9d-8dc4-6c1e39f86cc5

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL	UL 2238	E519602

Subject to changes. Please also observe the further product documentation!



Underwriters Laboratories Inc.

Downloads

Documentation

System Description

I/O-SYSTEM – SPEEDWAY, General Product Information

pdf
1.1 MB

[Download](#)

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 756-3106/040-025

URL [Download](#)

Power cable; M12A socket; angled; M12A plug; angled; 4-pole; Length: 2.5 m

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastra. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.