

Title of Change:	Qualify ON Semiconductor Vietnam (OSV) as an additional Automotive site for Assembly/Test of specified products in DPAK package.	
Proposed Changed Material First Ship Date:	21 September 2017	
Current Material Last Order Date:	N/A	
Current Material Last Delivery Date:	N/A	
Product Category:	Active components – Discrete components	
Contact information	Contact your local ON Semiconductor Sales Office or < <u>Phuong.Hoang@onsemi.com></u>	
Samples	Contact your local ON Semiconductor Sales Office to place sample order. Sample requests are to be submitted no later than 45 days after publication of this change notification.	
Sample Availability Date:	15 March 2017	
PPAP Availability Date:	15 May 2017	
Additional Reliability Data	Contact your local ON Semiconductor Sales Office or < <u>Cheanching.sim@onsemi.com>.</u>	
Type of Notification	This is a Final Product/Process Change Notification (FPCN) sent to customers. This FPCN is being issue months prior to implementation because this change provides an alternate source to an ON manufacturing facility utilizing the same BOM. ON Semiconductor will consider this proposed change and it's conditions acceptable, unless an inquir made in writing within 30 days of delivery of this notice. To do so, contact <pcn.support@onsemi.co< td=""></pcn.support@onsemi.co<>	
Change Category:	Type of Change	
Process – Assembly	Move of all or part of assembly to a different location/site/subcontractor.	
Process – Assembly	Change of product marking.	
Test Flow	Move of all or part of electrical wafer test and/or final test to a different location/site/subcontractor.	
Equipment	Production from a new equipment/tool which uses the same basic technology (replacement equipment or extension of existing equipment pool) without change of process.	

Description and Purpose:

This Final Notification announces the plan to qualify ON Semiconductor Vietnam (OSV) as an additional Assembly and Test site for operations of Automotive discrete DPAK packaged products.

Upon the expiration of this FPCN, new OSV part numbers will be available to allow specified products to be sourced from either the Seremban or Vietnam locations using the same Bill of Material.

ON Semiconductor Vietnam (OSV) is qualified site for DPAK Standard discrete packaged products and is ISO TS16949 certified.

Products sourced from OSV have been qualified to Automotive requirements and continue remain as Pb-free, Halide free and RoHS compliant.

Reason / Motivation for • Seamless dual source Mfg alternatives, ensuring capacity availability Change: • Instantaneous capacity available for growth; Short lead times; Lines down aversion • Risk for late release for customer: Limited capacity.
--

ON Semiconductor®



Final Product/Process Change Notification Document # : FPCN21107ZAD

Issue Date: 21 March 2017

	•	successfully ON Semicor	has been qualified and validated based on the same Product Specification. The device has y passed the qualification tests. Potential impacts can be identified, but due to testing performed by onductor in relation to the PCN, associated risks are verified and excluded. ated impacts.		
Sites Affect	ted:				
All site(s)	🗌 not applic	cable	 ☑ ON Semiconductor site(s) : ☑ Externa ON Seremban, Malaysia ON Dong Nai Province, Vietnam 	l Foundry/Subcon site	(s)
Marking of P Fraceability (m ON Semiconductor Vietnam (OSV) will be marked with s eremban device does not have site code marking.	ite code "VN" prior to	the date code
-	ata Summary:				
PACKAGE				Interval	Result
PACKAGE	: DPAK Specificati	ion	Condition	Interval	
PACKAGE Test HTRB	: DPAK Specificati JESD22-A1	on .08	Condition Ta = 175 °C, bias = 80% of rated V	1008 hrs	0/84
PACKAGE Test HTRB HTGB	E: DPAK Specificati JESD22-A1 JESD22-A1	08 08	Condition Ta = 175 °C, bias = 80% of rated V Ta = 175 °C, 100% max rated Vgss	1008 hrs 1008 hrs	
PACKAGE Test HTRB	: DPAK Specificati JESD22-A1	ion .08 .08 .03 .50)	Condition Ta = 175 °C, bias = 80% of rated V	1008 hrs	0/84 0/84
PACKAGE Test HTRB HTGB HTSL	E: DPAK Specificati JESD22-A1 JESD22-A1 JESD22-A1 MIL-STD-7 (M1037	ion .08 .08 .03 .50 .) 1	Condition Ta = 175 °C, bias = 80% of rated V Ta = 175 °C, 100% max rated Vgss Ta = 175 °C Ta=+25°C, deltaTj=100°C max,	1008 hrs 1008 hrs 1008 hrs	0/84 0/84 0/84
PACKAGE Test HTRB HTGB HTSL IOL	E: DPAK Specificati JESD22-A1 JESD22-A1 JESD22-A1 MIL-STD-7 (M1037 AEC-Q10	ion 08 08 03 50) 1 04	ConditionTa = 175 °C, bias = 80% of rated VTa = 175 °C, 100% max rated VgssTa = 175 °CTa=+25°C, deltaTj=100°C max, Ton = Toff = 2min	1008 hrs 1008 hrs 1008 hrs 1008 hrs 1008 hrs 15000 cyc	0/84 0/84 0/84 0/84
PACKAGE Test HTRB HTGB HTSL IOL TC	E: DPAK Specificati JESD22-A1 JESD22-A1 JESD22-A1 MIL-STD-7 (M1037 AEC-Q10 JESD22-A1	ion 08 08 03 50) 1 04 02	ConditionTa = 175 °C, bias = 80% of rated VTa = 175 °C, 100% max rated VgssTa = 175 °CTa=+25°C, deltaTj=100°C max, Ton = Toff = 2minTemp = -55°C to +150°C	1008 hrs 1008 hrs 1008 hrs 1008 hrs 15000 cyc 1000 cyc	0/84 0/84 0/84 0/84 0/84
PACKAGE Test HTRB HTGB HTSL IOL TC AC	E: DPAK Specificati JESD22-A1 JESD22-A1 JESD22-A1 MIL-STD-7 (M1037 AEC-Q10 JESD22-A1 JESD22-A1	ion .08 .08 .03 .50 .1 .04 .02 .01	Condition Ta = 175 °C, bias = 80% of rated V Ta = 175 °C, 100% max rated Vgss Ta = 175 °C Ta = 175 °C </td <td>1008 hrs 1008 hrs 1008 hrs 1008 hrs 15000 cyc 1000 cyc 96 hrs</td> <td>0/84 0/84 0/84 0/84 0/84 0/84</td>	1008 hrs 1008 hrs 1008 hrs 1008 hrs 15000 cyc 1000 cyc 96 hrs	0/84 0/84 0/84 0/84 0/84 0/84
PACKAGE Test HTRB HTGB HTSL IOL IOL TC AC H3TRB	E: DPAK Specificati JESD22-A1 JESD22-A1 JESD22-A1 JESD22-A1 (M1037 AEC-Q10 JESD22-A1 JESD22-A1 JESD22-A1	ion .08 .08 .03 .50 .01 .04 .02 .01 D-A113	Condition Ta = 175 °C, bias = 80% of rated V Ta = 175 °C, 100% max rated Vgss Ta = 175 °C Ta = 175 °C Ta=+25°C, deltaTj=100°C max, Ton = Toff = 2min Temp = -55°C to +150°C 121°C, 100% RH, 15psig, unbiased Temp = 85°C, RH=85%, bias = 80% of rated V	1008 hrs 1008 hrs 1008 hrs 1008 hrs 15000 cyc 1000 cyc 96 hrs	0/84 0/84 0/84 0/84 0/84 0/84 0/84



QV DEVICE NAME: MTD6N20ET4G (TMOS) PACKAGE: DPAK

Test	Specification	Condition	Interval	Result
HTRB	JESD22-A108	Ta = 150 °C, bias = 80% of rated V	1008 hrs	0/84
HTGB	JESD22-A108	Ta = 150 °C, 100% max rated Vgss	1008 hrs	0/84
HTSL	JESD22-A103	Ta = 150 °C	1008 hrs	0/84
IOL	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, deltaTj=100°C max, Ton = Toff = 2min	15000 cyc	0/84
тс	JESD22-A104	Temp = -55°C to +150°C	1000 сус	0/84
UHAST	JESD22-A118	Ta=130°C, P=18.8 PSIG, RH=85%	96 hrs	0/84
H3TRB	JESD22-A101	Temp = 85°C, RH=85%, bias = 80% of rated V	1008 hrs	0/84
PC	J-STD-020 JESD-A113	MSL 1 @ 260 °C		0/336
RSH	JESD22- B106	Ta = 265°C, 10 sec		0/30
SD	JSTD002	Ta = 245°C, 10 sec		0/15

NOTE: AEC-1pager is attached.

To access file attachments on pdf copy of PCN, please be guided by the steps below:

1. Download pdf copy of the PCN to your computer

2. Open the downloaded pdf copy of the PCN

3. Click on the paper clip icon available on the menu provided in the left/bottom portion of the screen to reveal the Attachment field

4. Then click on the attached file/s

Electrical Characteristic Summary:

Electrical characteristics are not impacted.

List of Affected Standard Parts:

Current SBN Part Number	New OSV Part Number	Qualification Vehicle
NTDV20N06LT4G	NTDV20N06LT4G-VF01	NTD110N02RT4G
NVD5414NT4G	NVD5414NT4G-VF01	NTD6414ANT4G MTD6N20ET4G