



10.7





NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0 SHELL: STEEL, TIN PLATED CONTACT: COPPER ALLOY, 15µ GOLD PLATED OPERATING TEMPERATURE: -55°C to +105°C

REALERER

(1)

CURRENT RATING: 3A PER CONTACT CONTACT RESISTANCE: 25mΩ MAX. INSULATOR RESISTANCE: 5000MΩ min. DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC rms

628 SERIES D-SUB CONNECTOR			SW REFERENCE NO.: 628 ASSEMBLY					
			DRAWN: C.B		DATE: AUG. 01/2018			18
			CHECKED:		DATE:			
	EDAC INC TORONTO, ONTARIO CANADA D QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: 1:1		SHEET	1	OF	1
			DRAWING NUMBER: 628-025-321-27			i-276 is		ISSUE
YOUR CONNECTION TO QU			PART NUMBER:	628-025-3	321-276			1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR R₀HS COMPLIANCY.