




P.C.B. MOUNTING HOLES

POS. 2



CIRCUIT: SPDT
CONTACT CONFIGURATION

SWITCH FUNCTION			
POS. 1	POS. 2	POS. 3	
<DN>	OFF	<DN>	
2-3	OPEN	2-1	

< > = MOMENTARY

- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: 0.00=±0.25
 3. TERM. NOS. FOR REF ONLY
 4. RATING: 3A @120VAC OR 28VDC; 1A @250VAC
 5. ELECTRIC LIFE: 30,000 MAKE AND BREAK CYCLES AT FULL LOAD
 6. INSULATION RESISTANCE: 1,000 MEGA-OHMS MIN
 7. DIELECTRIC STRENGTH: 1,000V RMS @SEA LEVEL
 8. OPERATING TEMP.: -30°C TO +85°C

E-SWITCH®

200 MSP-4 T1 B1 M2 Q E

REV.	ECN NO.	DESCRIPTION	DATE	CHKD
C	11498	REVISED ACTUATOR	5/11/01	CJB
B	11113	REVISED & REDRAWN	12/13/00	PML
		THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED		

TITLE	SCALE	DATE	DR	DWG	REV
200 MSP-4 T1 B1 M2 Q E	2:1	10/20/00	PML	T211083	C