



# Product: <u>6320UJ</u>

Fire Alarm, #18-2c BC, FPLP

## **Product Description**

Fire Alarm Cable, Plenum-FPLP, 2-18 AWG solid bare copper conductors with FEP insulation, Flamarrest® jacket with ripcord

### **Technical Specifications**

#### Product Overview

	6: F		iressable S	Systems, Ciro	uits: Audio, Contro	l, Initiating	, Notification
Construction D	etails						
Conductor							
	per of Element	Size Str	anding	Material			
Conductor(s) 2		18 AWG Sol	id B	C - Bare Co	oper		
Insulation							
Element	Materia	al	Nom.	Thickness	Nom. Insulation	Diameter	Color Code
Conductor(s) FEP -	Fluorinated Eth	ylene Propylen			0.054 in (1.4 mm)		Black, Red
Outer Shield							
Material							
No Shield							
Outer Jacket							
Material PVC - Polyvinyl Chlo	Nom. Thi		n. Diamete	r Ripcord Yes			
			0 111	163			
Overall Cable Diame	eter (Nominal): 0	0.138 IN					
Electrical Chara	acteristics						
Electrical Chara	acteristics						
		acitance Cond	-to-Cond	Max	c. Current		
Electricals			-to-Cond		<ol> <li>Current</li> <li>Conductor at 25℃</li> </ol>		
Electricals Nom. Conductor Do 6.78 Ohm/1000ft	CR Nom. Capa		-to-Cond				
Electricals Nom. Conductor Do 6.78 Ohm/1000ft Voltage	CR Nom. Capa		-to-Cond				
Electricals Nom. Conductor Do 6.78 Ohm/1000ft	CR Nom. Capa		-to-Cond				
Electricals Nom. Conductor Do 6.78 Ohm/1000ft Voltage UL Voltage Rating 300 V	CR Nom. Capa 26 pF/ft (85	i pF/m)	-to-Cond				
Electricals Nom. Conductor Do 6.78 Ohm/1000ft Voltage UL Voltage Rating 300 V	CR Nom. Capa 26 pF/ft (85	i pF/m)	-to-Cond				
Electricals Nom. Conductor Do 6.78 Ohm/1000ft Voltage UL Voltage Rating	CR Nom. Capa 26 pF/ft (85	i pF/m)	-to-Cond				
Electricals Nom. Conductor Do 6.78 Ohm/1000ft Voltage UL Voltage Rating 300 V Mechanical Char Temperature	CR Nom. Capa 26 pF/ft (85	i pF/m)	-to-Cond				
Electricals Nom. Conductor De 6.78 Ohm/1000ft Voltage UL Voltage Rating 300 V Mechanical Cha Temperature UL Temperature	CR Nom. Capa 26 pF/ft (85 aracteristics	i pF/m)	-to-Cond				
Electricals Nom. Conductor DG 6.78 Ohm/1000ft Voltage UL Voltage Rating 300 V Mechanical Cha Temperature UL Temperature 75°C 0	CR Nom. Capa 26 pF/ft (85 aracteristics	i pF/m)	-to-Cond				
Electricals Nom. Conductor DG 6.78 Ohm/1000ft Voltage UL Voltage Rating 300 V Mechanical Cha Temperature UL Temperature 75°C 0 Bend Radius	CR Nom. Capa 26 pF/ft (85 aracteristics Operating °C To +75°C	s pF/m)	-to-Cond				
Electricals Nom. Conductor D 6.78 Ohm/1000ft Voltage UL Voltage Rating 300 V Mechanical Char Temperature UL Temperature 75°C 0 Bend Radius Stationary Min. I	CR Nom. Capa 26 pF/ft (85 aracteristics	s pF/m)	-to-Cond				
Electricals Nom. Conductor D 6.78 Ohm/1000ft Voltage UL Voltage Rating 300 V Mechanical Char Temperature UL Temperature 75°C 0 Bend Radius Stationary Min. I	CR Nom. Capa 26 pF/ft (85 aracteristics Operating °C To +75°C nstallation Min. .10 in	s pF/m)	-to-Cond				

Bulk Cable Weight:	15 lbs/1000ft						
Standards and Compliance							
Environmental Suitability:	Indoor						
Flammability / Reaction to Fire:	NFPA 262 (UL910)						
NEC / UL Compliance:	Article 760, FPLP						
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)						
APAC Compliance:	China RoHS II (GB/T 26572-2011)						
Other Standard Compliance(s):	California State Fire Marshall						
Non-Plenum Number:	5320UJ						
Product Notes							
Notes:	Teflon® is a trademark of DuPont.						
History							
Update and Revision:	Revision Number: 0.309 Revision Date: 05-05-2023						

#### **Part Numbers**

Variants						
	ltem #	Color	UPC			
	6320UJ 0021000	Red	612825175759			

© 2023 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.