

SKH C64*2 (A&C) RH2

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Plug-in card holders are used to adapt cards from the Euro format (19") to connectors in compliance with IEC 603/ DIN 41612 and DIN 41617.

Plug-in card holders consist of the following components:

- Circuit board with standard connectors and inserts with clamping-yoke connection.
- Flange housing and holder/pull-out mechanism for the circuit card.
- Plug-in card and mounting foot for attaching to mounting rail or directly to panel.

The plug-in card holders are normally used in the following cases:

- For quick adaptation in industrial applications of different 19" modules, and for avoiding the expense of a 19" rack.
- When there are only a few cards to install and connect.
- The circuit board is located in a remote position where the cabling cannot be easily handled.
- An older system needs to be updated with additional electronics modules.
- For test devices, production processes and laboratories: where circuit boards need to be swapped out quickly and connections must be easy to handle.

General ordering data

| | |
|------------|---|
| Type | SKH C64*2 (A&C) RH2 |
| Order No. | 8013120000 |
| Version | Interface, Plug-in connector, acc. to DIN 41612 female, 64C |
| GTIN (EAN) | 4008190190798 |
| Qty. | 1 pc(s). |

SKH C64*2 (A&C) RH2

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|--------|--------|------------|--------|
| Length | 69 mm | Width | 286 mm |
| Height | 144 mm | Net weight | 673 g |

Temperatures

| | | | |
|-----------------------|-----------|---------------------|--------------|
| Operating temperature | 0...+55°C | Storage temperature | -40...+70 °C |
|-----------------------|-----------|---------------------|--------------|

Connection data

| | | | |
|--------------------------------|----------------|-------------------------------|--|
| Connection (field side) | LP2N 5.08mm | Connection on control side | Plug-in connector, acc. to DIN 41612 female |
| Number of poles (control side) | 64-pole female | Type (control side) | 64C |
| Contact assembly | a and c | Design of the pluggable board | 233x160 mm double euro format for 19" enclosures |

Rating data

| | | | |
|---------------|-------------------|------------------------------|-----|
| Rated voltage | 125V AC / 150V DC | Rated current per connection | 1 A |
|---------------|-------------------|------------------------------|-----|

Insulation coordination (EN50178)

| | | | |
|-------------------------------|--------------|--------------------------|----------|
| According to | DIN EN 50178 | Rated insulation voltage | 125 V AC |
| Surge voltage category | II | Pollution severity level | 2 |
| Pulse voltage test (1,2/50µs) | 1.1 kV | Insulation test voltage | 0.6 kVAC |

Connection field

| | | | |
|--------------------------------------|---------------------|--------------------------------------|----------------------|
| Type of connection | Screw connection | Clamping range, min. | 0.13 mm ² |
| Clamping range, max. | 6 mm ² | Solid, min. H05(07) V-U | 0.5 mm ² |
| Solid, max. H05(07) V-U | 6 mm ² | Flexible, min. H05(07) V-K | 0.5 mm ² |
| Flexible, max. H05(07) V-K | 4 mm ² | Flexible with sleeve, max. | 2.5 mm ² |
| Flexible with sleeve, min. | 0.5 mm ² | Sleeve with plastic collar, max. | 2.5 mm ² |
| Min. wire cross-section, AWG [field] | AWG 26 | Max. wire cross-section, AWG [field] | AWG 12 |
| Tightening torque, min. | 0.5 Nm | Tightening torque, max. | 0.6 Nm |
| Stripping length | 6 mm | | |

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC001419 | UNSPSC | 30-21-18-01 |
| eClass 5.1 | 27-24-22-04 | eClass 6.2 | 27-24-22-04 |
| eClass 7.1 | 27-14-11-52 | | |

Product information

| | |
|------------------------------|--|
| Descriptive text accessories | Kit for connection to TS35: Installation motherboard 205 1430000 and mounting foot TS35 0687900000 |
|------------------------------|--|

Approvals

Approvals



| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Creation date December 18, 2013 6:48:25 PM CET

SKH C64*2 (A&C) RH2

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

