

Note: This datasheet may be out of date.

Please download the latest datasheet of GJM0335C1E7R5WB01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GJM0335C1E7R5WB01%23

"#" indicates a package specification code.

# GJM0335C1E7R5WB01J













< List of part numbers with package codes > GJM0335C1E7R5WB01D GJM0335C1E7R5WB01W

#### GJM0335C1E7R5WB01J



### **Applications**

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment,Industrial
	Equipment,Mobile Electronics,Medical
	equipment [GHTF A/B/C] except for
	implant equipment,Automotive
	infotainment/comfort equipment
Specific	Please refer to Our Website and
Applications	specifications, etc. for information about
	the performance, functions, quality,
	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.



#### References

Packaging	Specifications	Standard Packing Quantity
D	φ180mm Reel Paper Tape	15000
W	φ180mm Reel W8P1 Paper Tape	30000
J	φ330mm Reel Paper Tape	50000

Mass (typ.)	
1 piece	0.33mg



## Appearance & Shape





1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# GJM0335C1E7R5WB01J

Note: This datasheet may be out of date.

Please download the latest datasheet of GJM0335C1E7R5WB01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GJM0335C1E7R5WB01%23

"#" indicates a package specification code.



## **Specifications**

Length	0.6±0.03mm	
Width	0.3±0.03mm	
Thickness	0.3±0.03mm	
Capacitance	7.5pF ±0.05pF	
Distance between external terminals g	0.2mm min.	
External terminal size e	0.1 to 0.2mm	
Operating Temperature Range	-55°C to 125°C	
Rated Voltage	25Vdc	
Size code in inch(mm)	0201 (0603M)	
TC	0±30ppm/°C	
Temperature characteristics	COC(FIA)	
(complied standard)	COG(EIA)	
Temperature range of	25°C to 125°C	
temperature characteristics		

2 of 2

#### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

