

## Specification Sheet

Part Number: 181-00597

Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



High Density Slotted Wall Wiring Duct, 1" x 1", Non-Adhesive, PVC, Black, 120ft/Carton

**Article Number** 181-00597

**Type** SLHD1X1

**Color** Black (BK)

**Quantity Per** carton

**Product Description** HellermannTyton Pro-Duct High-Density, Slotted-Wall Wiring Duct features narrow fingers equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

**Short Description** High Density Slotted Wall Wiring Duct, 1" x 1", Non-Adhesive, PVC, Black, 120ft/Carton

|   |                         |
|---|-------------------------|
| <b>Global Part Name</b>                 | SLHD1X1-PVC-BK          |
| <b>Technical Description</b>            | Non-Adhesive            |
| <b>Length L (Imperial)</b>              | 6.0                     |
| <b>Length L (Metric)</b>                | 1.83                    |
| <b>Fixation Method</b>                  | Non-Adhesive            |
| <b>Width W (Imperial)</b>               | 1.0                     |
| <b>Width W (Metric)</b>                 | 25.4                    |
| <b>Height H (Imperial)</b>              | 1.06                    |
| <b>Height H (Metric)</b>                | 26.9                    |
| <b>Mounting Hole Centers (Imperial)</b> | 2.0                     |
| <b>Material</b>                         | Polyvinylchloride (PVC) |
| <b>Material Shortcut</b>                | PVC                     |
| <b>Flammability</b>                     | Self-Extinguishing      |
| <b>Halogen Free</b>                     | No                      |

|                                     |  |
|-------------------------------------|--|
| <b>Operating Temperature</b>        | +122°F (+50°C)                                   |
| <b>Reach Compliant (Article 33)</b> | No   |
| <b>ROHS Compliant</b>               | Yes  |
| <b>Certification/Specification</b>  | EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A CSA UL |
| <b>UL Recognized (US)</b>           | Yes  |
| <b>Package Quantity (Imperial)</b>  | 120  |
| <b>Package Quantity (Metric)</b>    | 36.58  |
| <b>Customs Number</b>               | 3925900000                                       |

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)