




.XXX ±0.05

DO NOT MAKE MANUAL REVISIONS TO MASTER.

$\land \neg$	
$X \mid \Box \mid$	C







NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED


OPERATING TEMPERATURE:

20A (CURRENT) (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

DIELECTRIC WITHSTANDING VOLTAGE:



	COMBINATION D-SUB			SW REFERENCE NO.: 629 COMBO ASSEMBLY				
				DRAWN: C.B		DATE: JAN. 01/2019		19
				CHECKED:		DATE:		
		EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (IN C.A.D. 1	:1)	SHEET 1	OF	2
	TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 629-3W3-		3-250-2T1		ISSUE	
YOUR CONNECTION TO			QUALITY & SERVICE	PART NUMBER:	629-3W3-	-250-2T1		1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY. COMPLIANT

-55°C ~ 125°C

POWER/CO-AX CONTACT RATING:

INSULATOR RESISTANCE:

5000MΩ min. 1000V AC rms

