Mallory Sonalert Products, Inc.				Part #: JT120-YG-CSI		Γ120-YG-CSL	
Sales Outline Drawing				Revision:		С	
pecifications:							
	1	1 2	<u> </u>	I		T	
Stack Number: LED Color:	1 YELLOW	2 GREEN					
		II.					
Connection Wires:	Yellow and Brown	Green and Brown					
LED Current Draw:	<230 mA	<190 mA					
Rated Voltage:			120 VAC				
Operating Voltage:			90-120 VAC				
Sound Level Category:	Loud	Loud	Loud		Loud		
Mode of Operation:	Continuous	Medium Pulse (5PPS)	Double Pulse (0.	5PPS)	Continuous	for 5 sec then 0.1s beep un reset	
Connection:	Black and Gray Wires	Black and Gray Wires; Orange wire connected to	Black and Gray Wire wire connected to Gray wire	ected to Green/Yellow wires connec		Gray wires; Orange and Purp nected to Green/Yellow wire	
Sound Current Draw:	40mA Max.	40mA Max.	40mA Max			40mA Max.	
Loudness @ 1m:	TOTAL WILLY.	TOTAL WAY	80-85 dB(A) Ty		1	70mm (maxi	
Frequency:			2000 ± 500 H				
Total Max Current:		-160	A with all LED's and so		rking		
		<40UM	-25° ~ +60°C		ıkılığ		
Operating Temperature:							
Lens Color:		Opaque White					
Material:	ABS FR15U						
Mounting Method:	Stainless Steel Pole						
Weight Typical (g):	690						
NEMA 12:	Approved						
Options:			Please contact fac	ctory.			
/— YELLOW							
				GAS	KET	48° wine	
		18.1 [459.8]————	ø0.20	GAS		4.6]	
		18.1 [459.8]—————	3 pl #10 or 5mm screws for mounting	[ø5.2] aces		4.6] es	
GREEN		18.1 [459.8]————	3 pl #10 or 5mm screws for	[Ø5.2] aces	0.57 [Ø1. for wire	4.6] es - 51.9]	
2.4 [61.8] 2.7 [68.3] TOP VIEW			3 pt #10 or 5mm screws for mounting 0.39 [9.9]	[Ø5.2] aces MDUNTII DIAGRA	0.57 [Ø1. for wire	4.6] es - 51.9]	
2.4 [61.8] 2.7 [68.3] TOP VIEW			3 pt #10 or 5mm screws for mounting 0.39 [9.9]	[Ø5.2] aces MDUNTII DIAGRA	0.57 [Ø1. for wire	4.6] es - 51.9]	
2.4 [61.8] 2.7 [68.3] TOP VIEW	T STACK COLOR WIR		3 pt #10 or 5mm screws for mounting 0.39 [9.91 0.95 [24.	[Ø5.2] aces MOUNTII DIAGRA	0.57 [Ø] for wire 2.04 [4.6] es - 51.9]	
2.4 [61.8] 2.7 [68.3] TOP VIEW CONNECTOR	T STACK COLOR WIR	E TO POWER AND BE D BLACK WIRES TO F	3 pt #10 or 5mm screws for mounting 0.39 [9.91 0.95 [24.	(Ø5.2) aces 33 MOUNTI DIAGRA	0.57 [Ø1. for wire 2.04 [4.6] es - 51.9]	
D OPERATION: CONNEC	T STACK COLOR WIR CONNECT GRAY AN FOR MEDIUM PULSE	E TO POWER AND BE D BLACK WIRES TO F E, CONNECT GRAY &	3 pt #10 or 5mm screws for mounting 0.95 [24.	(Ø5.2) aces 331 MOUNTII DIAGRAI	90.57 [Ø1. for wire 2.04 [0.95 [2.04] JND. BE WIRE TO	4.6] es - 51.9] - 4.3]	