



Electrical Characteristics

Nominal Impedance: Non Constant
 Frequency Range: DC to 100 MHz
 Insulation Resistance: 5000 megohms minimum

Mechanical Characteristics

Mating Cycles: 500 cycles minimum

NOTES: UNLESS OTHERWISE SPECIFIED

- BRASS PER JIS-H3250 C3604
- BERYLLIUM COPPER PER JIS-1730B
- TEFLON: MIL-P-22296B
- PART TO BE CLEAN AND FREE OF BURRS

NO	DESCRIPTION	MATERIAL	Q'TY	FINISH
15	NUT	BRASS	1	NICKEL 100µ" MIN.
14	WASHER	BRASS	1	NICKEL 100µ" MIN.
13	GASKET	RUBBER	1	NONE
12	SLEEVE	BRASS	1	NICKEL 100µ" MIN.
11	SLEEVE	BRASS	1	NICKEL 100µ" MIN.
10	WASHER	BRASS	1	NICKEL 100µ" MIN.
9	SPRING	SK-5	2	NICKEL 100µ" MIN.
8	INSULATION	PBT	1	NONE
7	WASHER	BRASS	1	NICKEL 100µ" MIN.
6	GASKET	RUBBER	1	NONE
5	INSULATION	PBT	1	NONE
4	BODY	BRASS	1	NICKEL 100µ" MIN.
3	SHELL	BRASS	1	NICKEL 100µ" MIN.
2	PIN II	Be Cu	1	GOLD
1	PIN I	BRASS	1	GOLD
NO	DESCRIPTION	MATERIAL	Q'TY	FINISH

For stripping and assembly instructions see Drawing Number: VAIB1206



Cinch Connectivity Solutions;
 7-13 Russell Way,
 Widford Industrial Estate,
 Chelmsford, Essex,
 CM1 3AA, UK.
 Tel: +44 (0) 1245 359515
 Fax: +44 (0) 1245 358938

SCALE: Not To Scale

DIMENSIONS: mm

TOLERANCES:
 ± 0.2mm unless
 otherwise stated

DRAWN BY: S Nash
 CHECKED BY: S Nash
 APPROVED BY: P D Couzens
 DATE: 03 May 02

TITLE:
**Twin BNC Clamp Plug for
 RG108**

PART NUMBER:
VBT10-2031

PAGE: 1 of 1

First Issue	SN	1	03 May 02
DESCRIPTION OF REVISION	APPVD	ISS	DATE