

Cable - CAB-M104CFM/OE/22/S/30M - 2909794


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Your advantages

- Individual wire marking: 1, 2, 3, 4, etc.
- Individual wires fitted with ferrules
- Open end at one end
- 1:1 connection



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 055626 682853
GTIN	4055626682853

Technical data

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Max. permissible operating voltage	125 V AC
	125 V DC
Max. current carrying capacity per path	2 A
Length of cable	1 m
External cable diameter	14.1 mm
Single wire, cross section	0.36 mm ²
Single wire, cross section [AWG]	22
Shielding	yes
	Overall foil and braid shield

Connection data

Connection name	Field level
Connection method	Connector
Number of connections	1
Number of positions	104

Cable - CAB-M104CFM/OE/22/S/30M - 2909794

Technical data

Connection data 2

Connection name	Controller level
Connection method	Single wires
Number of positions	49
Note	The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.

Supported controller

Controller	APACS
------------	-------

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>