


## L0603B2R2MDWFT

## Aliases (L0603B2R2MDWFT)

Not for New Design • Scheduled EOL - Last date to buy 30 JUN 2023 KEMET, L-DWF, Power, 2.2 uH, 20%



## Click here for the 3D model.

0603
1.6mm +/-0.2mm
0.8mm +/-0.2mm
0.8mm +/-0.2mm
0.4mm +/-0.15mm
0.4mm +/-0.15mm

Packaging Specifications		
Packaging	T&R	
Packaging Quantity	3000	

General Information			
Series	L-DWF		
Style	SMD Chip		
Description	Surface Mount Inductor		
Features	Bottom Surface Electrode		
RoHS	Yes		
Notes	Last Order Date June 30, 2023. Suggested Replacement - https://productfinder.pulseelectronics.com/part/BKPB001608DZ2R2MA2.		

Specifications	
Inductance	2.2 uH (7.96 MHz)
Inductance Tolerance	20%
Temperature Range	-40/+105°C
Current	190 mAmps (Isat, 30% Drop In Inductance), 560 mAmps (Irms, 40C Rise By Self Heating)
DC Resistance	0.17 Ohms
Self-Resonant Frequency	80 MHz

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.