

T495A106M010ZTE2K07280

Obsolete

B450, Tantalum, MnO₂ Tantalum, 10 uF, 20%, 10 VDC, SMD, Molded, Low ESR, Surge Robust, 2 Ohms, 3216, Height Max = 1.8mm



General Information

| | |
|-------------|-----------------------------------------------------------|
| Series | B450 |
| Dielectric | MnO ₂ Tantalum |
| Style | SMD Chip |
| Description | SMD, Molded, Low ESR, Surge Robust |
| Features | Low ESR, Surge Robust |
| RoHS | Yes |
| Termination | Tin |
| AEC-Q200 | No |
| Notes | Obsolete. Old Part Number [Obsolete] Was B45010A1066M208. |

Specifications

| | |
|-----------------------|---------------------------------------------------|
| Capacitance | 10 uF |
| Capacitance Tolerance | 20% |
| Voltage DC | 10 VDC (85C), 6.7 VDC (125C) |
| Temperature Range | -55/+125°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 6% |
| Failure Rate | N/A |
| Resistance | 2 Ohms (100kHz) |
| Ripple Current | 190 mAmps (25C), 171 mAmps (85C), 76 mAmps (125C) |
| Leakage Current | 1 uA |

Dimensions

| | |
|-----------|----------------|
| Footprint | 3216 |
| L | 3.2mm +/-0.2mm |
| W | 1.6mm +/-0.2mm |
| H | 1.6mm +/-0.2mm |
| S | 0.8mm +/-0.3mm |
| F | 1.2mm +/-0.1mm |
| K | 1.3mm TYP |

Packaging Specifications

| | |
|--------------------|------------|
| Packaging | T&R, 330mm |
| Packaging Quantity | 9000 |