

Contact Dimensions: 500-Wire Hole .050x.025(1.27x0.64) - Tail LG=.260(6.60) .100 (2.54) Contact Spacing x .200 (5.08) Row Spacing

1





- INSULATOR MATERIAL: THERMOPLASTIC PBT BLACK, UL 94V-0
- CONTACT MATERIAL; COPPER TIN ALLOY CONTACT PLATING: GOLD ON THE MATING AREA, TIN PLATING ON THE CONTACT TAILS, NICKEL UNDERPLATE





	ACAD REFERENCE NO. 345-ENG-MASTER			
	DRAWN: R.STA.MONICA	DATE: MA	Y.16/2017	
	CHECKED:	DATE:		
	SCALE: 1:1	SHEET '	OF 2	
)	DRAWING NUMBER		ISSUE	
	345-ENG-MASTER		1	

SECTION A-A

.330[8.38] CARD SLOT 160[4.06] POINT OF CONTACT









Contact Code 558

Contact Code 559

Contact Code 560

INSULATOR MATERIAL: THERMOPLASTIC POLYESTER, UL 94V-0

DAP MATERIAL AVAILABLE UPON REQUEST

CONTACT MATERIAL; COPPER ALLOY CONTACT PLATING: GOLD ON THE MATING AREA, TIN PLATING ON THE CONTACT TAILS, NICKEL UNDERPLATE

345/395 SERIES CARD EDGE CONNECTOR CONTACT CODE 555,556,558,559,560 DIMENSIONS

YOUR CONNECTION TO QUALITY & SERVICE

	ACAD REFERENCE NO. 345-ENG-MASTER			
	DRAWN: R.STA.MONICA	DATE:MAY.16/2017		
•	CHECKED:	DATE:		
	SCALE: 1:1	SHEET 2 OF 2		
D	DRAWING NUMBER	ISSUE		

345-ENG-MASTER