

# GMA.0B.045.DA

## **SUMMARY**

#### # Wires



Image is for illustrative purpose only

Series	OB
Termination type	No contacts / Accessory
IP rating	0
AWG wire size	0.00 - 0.00
Cable Ø	4.50 - 5.20 mm
Status	active

### Download

Request a quote Catalog

## **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model	GMA*: Bend relief Blue
Keying	No keying
Housing Material	Thermoplastic polyurethane elastomer (Elastollan 1185 A)
Variant	A : Blue
Weight	.43 g
Performance	

#### Performance

Configuration Insulator Rated Current

#### Others

Temp (min / max): -40°C / +80°C

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

### DRAWINGS



No keying

#### Dimensions

	А	L
mm.	4.5	24
in.	0,18	0,94

### **RECOMMENDED BY LEMO**

Tools

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.